

# Monitor

## RX-22



### KEY FEATURES

- dedicated to continuous operation (24/7)
- LED backlight
- Glass shield protecting LCD panel
- Function preventing from burning-in static images on the LCD panel

### LCD PANEL

Panel Type	TFT, LED backlight
Screen Size (Diagonal)	21.5"
Panel Resolution	1920 x 1080
Format	16:9
Brightness	250 cd/m <sup>2</sup>
Contrast Ratio	1000:1
Viewing Angle (H/V)	85°/80°
Response Time	3 ms
Display Color	16.7 mln

### OTHER FUNCTIONS

OSD	languages: Polish, English, Russian, others
Digital Filter	3D
Built-in Speakers	2 x 2 W

### INTERFACES

Video Input	2 x CVBS, BNC connector (loop-through), 1 x VGA, 1 x S-Video, 1 x HDMI, 1 x DVI
Audio Input	1 x Mini Jack stereo, 2 x RCA (loop-through)

### INSTALLATION PARAMETERS

Dimensions (mm)	513 (W) x 369 (H) x 155 (D)
Weight	6.9 kg
Case	black, metal , glass shield protecting LCD panel
Power Supply	12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)
Power Consumption	25 W (max)
Operating Temperature	0°C ~ 40°C
Mounting Standard	VESA 100 x 100 mm • VESA 75 x 75 mm