

noVus

Monitor

NVM-622LCD

LCD 600 *series*



KEY FEATURES

- dedicated to continuous operation (24/7)
- LED backlight
- Glass shield protecting LCD panel
- Function preventing from burning-in static images on the LCD panel
- Convenient access to connectors
- Wall mount installation without additional brackets

DIMENSIONS



LCD PANEL

Panel Type	TFT, LED backlight
Screen Size (Diagonal)	21.5"
Panel Resolution	1920 x 1080
Format	16:9
Brightness	250 cd/m2
Contrast Ratio	1000:1
Viewing Angle (H/V)	85°/80°
Response Time	5 ms
Display Color	16.7 mln

OTHER FUNCTIONS

OSD	languages: Polish, English, Russian, others
Digital Filter	3D
Built-in Speakers	2 x 1 W

INTERFACES

Video Input	2 x CVBS, BNC connector (loop-through), 1 x VGA, 1 x S-Video, 1 x HDMI
Audio Input	1 x Jack stereo (loop-through)

INSTALLATION PARAMETERS

Dimensions (mm)	513 (W) x 404 (H) x 197 (D)
Weight	5.1 kg
Case	black, plastic , glass shield protecting LCD panel
Power Supply	12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)
Power Consumption	28 W (max)
Operating Temperature	0°C ~ 40°C
Mounting Standard	VESA 100 x 100 mm

