

Digital Video Recorder NDR-BA6208



KEY FEATURES

960H

**WD1 Real-Time
RECORDING**



- Video channels: 8, audio channels: 4
- Recording speed up to 200 fps
- Internal HDDs mount: up to 2
- Monitor outputs: 4 (3 x main, 1 x spot)
- Advanced network software
- Supports 700 TVL cameras (960H)

COMPLIANCE



DIMENSIONS



VIDEO

Video Input	8 x BNC
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI, 1 x VGA, 1 x BNC • spot (full screen, sequence): 1 x BNC

AUDIO

Audio Input/Output	4 x RCA/1 x RCA
--------------------	-----------------

RECORDING

Compression	H.264
Recording Speed	200 fps (960 x 576) • 200 fps (720 x 576) • 200 fps (720 x 288) • 200 fps (360 x 288)
Recording Mode	time-lapse, triggered by: REC/PANIC button, alarm input, motion detection
Schedule	individual settings for: each camera, each day of the week, configuration with an accuracy of: 60 min, possibility of combining individual recording modes
Prealarm/Postalarm	up to 30 s/up to 5 min

PLAYBACK

Playback Speed	200 fps (25 fps per channel)
Recorded Data Search	by date/time, events

BACKUP

Backup Methods	DVD (option), USB port (HDD or Flash memory), network
Backup File Format	AVI, DAT

STORAGE

Internal storage	available mount: 2 x HDD 3.5" SATA (without DVD-RW) *
Total Capacity	8 TB
DVD-RW	1 x SATA (option)

ALARM

Alarm Input/Output	8/1 relay type
Motion Detection	22 x 15 grid, individual settings of sensitivity
System Reaction to Alarm Events	buzzer, e-mail, alarm output activation, screen message, recording activation

NETWORK

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
PC/MAC Software	B-Viewer, CMS, NMS, Internet Explorer/-
Mobile applications	SuperLivePro (iPhone, Android), SuperLiveHD (iPhone, Android)

Digital Video Recorder

NDR-BA6208

Max. Number of Connections with DVR 7 (live monitoring: 5, playback: 1, configuration: 1)

PTZ

PTZ Ports	1 x RS-485
PTZ Protocols	N-Control, Pelco-D, Pelco-P, others
PTZ Functions	pan/tilt/zoom, preset commands, patterns, tours, auto-scans

AUXILIARY INTERFACES

USB Ports	2 x USB 2.0
-----------	-------------

OPERATING SYSTEM

Operating System	Linux
Operation Mode	quadplex
OSD	languages: Polish, English, Russian, others
Control	front panel, PC mouse and IR remote controller (in-set included), network, NV-KBD70, NV-KBD50, NV-KBD30 keyboards
System Diagnostic	automatic control of: HDDs

INSTALLATION PARAMETERS

Dimensions (mm)	430 (W) x 65 (H) x 390 (D)
Weight	4 kg (without HDDs)
Power Supply	12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)
Power Consumption	40 W (with 2 HDDs)
Operating Temperature	0°C ~ 50°C

* List of compatible HDD models and maximum of their capacities is available in section **DOWNLOADABLE FILES**.