

IP Recorder NVR-3416

6000 VSS IP



KEY FEATURES




- 8 x PoE Ethernet ports
- 16 x video and audio channels
- Recording speed up to 480 fps at 2048 x 1536
- Supports resolution up to 2048 x 1536
- Recorded stream size: 54 Mb/s in total from all cameras
- 2 x internal place for HDD mounting
- 3 x monitor outputs (HDMI, VGA, BNC)
- Intelligent image analysis

COMPLIANCE



DIMENSIONS



VIDEO

Maximum Supported Camera Resolution	2048 x 1536
Compression	H.264, H.264+
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI, 1 x VGA, 1 x BNC (up to 3 monitors simultaneously)
Dualstreaming Support	yes*

AUDIO

Audio Input/Output	- / 1 x line-out (BNC)
--------------------	------------------------

RECORDING

Recording Speed	480 fps (16 x 30 fps for 1280 x 720) • 480 fps (16 x 30 fps for 1920 x 1080) • 480 fps (16 x 30 fps for 2048 x 1536)
Stream Size	112 Mb/s in total from all cameras
Recording Mode	continuous, triggered by: alarm input, motion detection, perimeter intrusion detection
Schedule	individual settings for: each camera, each day of the week, configuration with an accuracy of: 1 min, possibility of combining individual recording modes
Prealarm/Postalarm	up to 32 MB/do 300 s

DISPLAY

Display Speed	480 fps (16 x 30 fps)**/**
---------------	----------------------------

PLAYBACK

Playback Speed	300 fps (10 x 30 fps for 1280 x 720) • 90 fps (3 x 30 fps for 1920 x 1080) • 30 fps (1 x 30 fps for 2048 x 1536)
Recorded Data Search	by date/time, image analysis events

BACKUP

Backup Methods	USB port (HDD or Flash memory), network, cloud storage
Backup File Format	AVI, DAV

STORAGE

Internal Storage	available mount: 2 x HDD 3.5" 6 TB SATA
Total Internal Capacity	12 TB

ALARM

Internal Alarm Input/Output	8/3 relay type (max. 12VDC/1A)
Camera Alarm Input/Output	supports IP camera's alarm input/output *
Motion Detection	supports camera's motion detection*

IP Recorder NVR-3416

System Reaction to Alarm Events buzzer, e-mail, alarm output activation, screen message, recording activation, PTZ, cloud storage

INTELLIGENT IMAGE ANALYSIS

Perimeter intrusion detection 2 channels ****

Face detection 1 channel ****

NETWORK

Network Interface 1 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s • 8 x Ethernet PoE (IEEE802.3af, Class 3) - RJ-45 interface, 10/100 Mbit/s

Network Protocols Support HTTP, TCP/IP, IPv4, UDP, FTP, DHCP, DNS, DDNS, NTP, UPnP, SMTP

ONVIF Protocol Support S profile (ONVIF 2.2 or higher)

PC/MAC Software Internet Explorer, Firefox, Chrome/-

Mobile applications VSS Mobile (iPhone, Android)

Number of Simultaneous Connections up to 10 clients

Bandwidth 28 Mb/s in total to all client workstations - with image analysis • 58 Mb/s in total to all client workstations - without image analysis

PTZ

PTZ Functions pan/tilt/zoom, preset commands*

AUXILIARY INTERFACES

USB Ports 2 x USB 2.0

OPERATING SYSTEM

Operating System Linux

Operation Mode triplex

OSD languages: Polish, English, Russian, others

Control front panel, IR remote controller (in-set included), PC mouse (in-set included), network

System Diagnostic automatic control of: HDDs, network, camera connection loss

Security password protection, IP filtering

INSTALLATION PARAMETERS

Dimensions (mm) 360 (W) x 48 (H) x 260 (D)

Weight 2 kg (without HDD)

Power Supply 48 VDC (100 ~ 240 VAC/48 VDC PSU in-set included) • 12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)

Power Consumption 40 W (with 2 HDDs) + 90 W PoE

Operating Temperature -10°C ~ 55°C

* Function capability depends on used camera, for details please check the compatibility list.

** For BNC output speed may be lower.

*** Available with dual streaming mode.

**** The "Perimeter intrusion detection" and "Face Detection" cannot run simultaneously.

***** List of compatible HDD models and maximum of their capacities is available in section **DOWNLOADABLE FILES**.