

AHD Recorder

NHDR-3108AHD



3000
AHD SERIES

KEY FEATURES

720p Real-Time
RECORDING



- Video channels: 8, audio channels: 4
- Recording speed up to 200 fps **
- Internal HDDs mount: up to 1
- Monitor outputs (main): 2
- Advanced network software
- Supports 700 TVL analog cameras (960H)
- Supports HD analog cameras (720p)

COMPLIANCE



DIMENSIONS



VIDEO

Video Input	8 x BNC
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI (FullHD), 1 x VGA (FullHD)

AUDIO

Audio Input/Output	4 x RCA (Line-in)/1 x HDMI, 1 x RCA
--------------------	-------------------------------------

RECORDING

Compression	H.264
Recording Speed **	200 fps (464 x 288) • 200 fps (928 x 288) • 200 fps (928 x 576) • 200 fps (1280 x 720)
Recording Mode	continuous, triggered by: REC/PANIC button, motion detection
Schedule	individual settings for: each camera, each day of the week, configuration with an accuracy of: 30 min, possibility of combining individual recording modes
Prealarm/postalarm	up to 3 s/up to 5 min

PLAYBACK

Playback Speed	120 fps
Recorded Data Search	by date/time, events, object appearance/disappearance

BACKUP

Backup Methods	USB port (HDD or Flash memory), network
Backup File Format	BMP, AVI, H264

STORAGE

Internal storage	available mount: 1 x HDD 3.5" SATA ***
Total Internal Capacity	6 TB

ALARM

System Reaction to Alarm Events	buzzer, e-mail, screen message, recording activation
---------------------------------	--

NETWORK

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
PC/MAC Software	NMS, Internet Explorer, NHDR-5000 Viewer, Firefox, Opera/Safari
Mobile applications	RXCamLink (iPhone, Android)
Number of Simultaneous Connections up to 3 (live monitoring: 3, playback: 3, configuration: 3)	

PTZ

PTZ Ports	1 x RS-485
PTZ Protocols	Pelco-D, Pelco-P



AHD Recorder NHDR-3108AHD

PTZ Functions pan/tilt/zoom, preset commands, patterns

AUXILIARY INTERFACES

USB Ports 2 x USB 2.0

OPERATING SYSTEM

Operating System Linux

OSD languages: Polish, English

Control front panel, PC mouse and IR remote controller (in-set included),
network, NV-KBD50 keyboard

System Diagnostic automatic control of: HDDs

INSTALLATION PARAMETERS

Dimensions (mm) 300 (W) x 53 (H) x 227 (D)

Weight 1.1 kg (without HDD)

Power Supply 12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)

Power Consumption 20 W (with 1 HDD)

Operating Temperature -10°C ~ 45°C

* Support both high definition analog cameras (720p) and standard resolution cameras (960H). Detailed information in user's manual.

** Recording is limited to 15 fps per channel during playback.

*** List of compatible HDD models and maximum of their capacities is available in section DOWNLOADABLE FILES.

