

Bullet AHD Camera NVAHD-2DN5102H/IR-1

5000
AHD SERIES



KEY FEATURES



KEY FEATURES

- D/N function - IR cut filter
- resolution 1080p
- Lens: varifocal, $f=2.8 \sim 12$ mm/F1.2
- optional UTC remote controller
- Min. Illumination from 0.0001 lx (0 lx, IR on)
- IR LED, range up to 20 m

DIMENSIONS



IMAGE

Image Sensor	CMOS sensor 1/2.9" SONY
Operating mode	AHD 1080p, analog 960H
Number of Effective Pixels	1920 (H) x 1080 (V)
Resolution	1080p
Min. Illumination	0.5 lx/F1.2 - color mode • 0.01 lx/F1.2 - B/W mode • 0.001 lx/F1.2 - color mode (DSS) • 0.0001 lx/F1.2 - B/W mode (DSS) • 0 lx (IR on) - B/W mode
S/N Ratio	> 52 dB (AGC off)
Electronic Shutter	auto/manual: 1/25 s ~ 1/50000 s (AHD), , 1/50 s ~ 1/50000 s (analog 960H)
Digital Slow Shutter (DSS)	up to 30x
High Light Compensation (HLC)	yes
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes

LENS

Lens Type	varifocal, $f=2.8 \sim 12$ mm/F1.2
-----------	------------------------------------

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual
Switching Level Adjustment	yes
Switching Delay	0 ~ 60 s
Visible Light Sensor	yes

OTHER FUNCTIONS

OSD	languages: Polish, English, Russian, others
Privacy Zones	4
Motion Detection	yes
Image Processing	180° image rotation, sharpening, mirror effect
Remote control	Yes (optional UTC remote control)*

IR LED

LED Number	40
Range	20 m
Angle	120°

INTERFACES

Video Output	BNC, 1.0 Vp-p, 75 Ohm
--------------	-----------------------

INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 88 (W) x 88 (H) x 220 (L)
Weight	0.53 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, ivory, fully cable managed wall mount bracket in-set included
Power Supply	12 VDC
Power Consumption	1 W • 3.3 W (IR illuminator on)
Operating Temperature	-30°C ~ 40°C

** Note: UTC functionality available on cameras with serial numbers starting from: 150611xxxx
Remote controller type: NV-RCUTC-35HD*