

Bullet AHD Camera NVAHD-1DN3102H/IR-1




KEY FEATURES



KEY FEATURES

- D/N function - IR cut filter
- resolution 720p
- optional UTC remote controller
- Min. Illumination from 0.0013 lx (0 lx, IR on)
- IR LED, range up to 30 m

DIMENSIONS



IMAGE

Image Sensor	CMOS sensor 1/4" APTINA
Operating mode	AHD 720p, analog 960H
Number of Effective Pixels	1280 (H) x 800 (V)
Resolution	720p
Min. Illumination	0.03 lx/F1.2 - color mode • 0.0013 lx/F1.2 - B/W mode • 0 lx (IR on) - B/W mode
S/N Ratio	> 60 dB (AGC off)
Electronic Shutter	auto/manual: 1/25 s ~ 1/50000 s (AHD), , 1/50 s ~ 1/50000 s (analog 960H)
Digital Slow Shutter (DSS)	up to 30x
High Light Compensation (HLC)	yes
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes

LENS

Lens Type	varifocal, f=2.8 ~ 12 mm/F1.2
-----------	-------------------------------

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual
Switching Level Adjustment	yes
Switching Delay	0 ~ 60 s
Visible Light Sensor	yes

OTHER FUNCTIONS

OSD	languages: Polish, English, Russian, others
Privacy Zones	4
Motion Detection	yes
Image Processing	180° image rotation, sharpening, mirror effect
Remote control	Yes (optional UTC remote control)*

IR LED

LED Number	2
Range	30 m
Angle	60°

INTERFACES

Bullet AHD Camera NVAHD-1DN3102H/IR-1

Video Output BNC, 1.0 Vp-p, 75 Ohm

INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 77 (W) x 65 (H) x 178 (L)
Weight	0.53 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, ivory, fully cable managed wall mount bracket in-set included
Power Supply	12 VDC
Power Consumption	1 W • 3.8 W (IR illuminator on)
Operating Temperature	-20°C ~ 50°C

** Note: UTC functionality available on cameras with serial numbers starting from: 2015083061*