

## Bullet AHD Camera

### NVAHD-2DN5104H/IRH-2

**5000**  
AHD SERIES



#### KEY FEATURES



#### KEY FEATURES

- D/N function - IR cut filter
- resolution 1080p
- Lens: varifocal, f=2.8 ~ 12 mm/F1.2
- Smart IR function
- Convenient lens adjustment
- optional UTC remote controller
- Min. Illumination from 0.01 lx (0 lx, IR on)
- IR LED, range up to 40 m

#### DIMENSIONS



#### IMAGE

Image Sensor	CMOS sensor 1/3" SONY
Operating mode	AHD 1080p, analog 960H
Number of Effective Pixels	1920 (H) x 1080 (V)
Resolution	1080p
Min. Illumination	0.5 lx/F1.2 - color mode • 0.01 lx/F1.2 - B/W mode • 0 lx (IR on) - B/W mode
S/N Ratio	> 80 dB (AGC off)
Electronic Shutter	auto/manual: 1/25 s ~ 1/50000 s (AHD), , 1/50 s ~ 1/50000 s (analog 960H)
Digital Slow Shutter (DSS)	up to 30x
High Light Compensation (HLC)	yes
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes

#### LENS

Lens Type varifocal, f=2.8 ~ 12 mm/F1.2

#### DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual
Switching Level Adjustment	yes
Switching Delay	0 ~ 60 s
Visible Light Sensor	yes

#### OTHER FUNCTIONS

OSD	languages: Polish, English, Russian, others
Privacy Zones	4
Motion Detection	yes
Image Processing	180° image rotation, sharpening, mirror effect
Remote control	Yes (optional UTC remote control)*

#### IR LED

LED Number	2
Range	40 m
Angle	90°

#### INTERFACES

**Bullet AHD Camera  
NVAHD-2DN5104H/IRH-2**

Video Output BNC, 1.0 Vp-p, 75 Ohm

**INSTALLATION PARAMETERS**

Dimensions (mm)	with bracket: 109 (W) x 111 (H) x 259 (L)
Weight	0.996 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included
Power Supply	12 VDC, 24 VAC
Power Consumption	1 W • 7 W (IR illuminator on) • 14.2 W (IR and heater on)
Operating Temperature	-30°C ~ 50°C
Built-in Heater/Fan	yes/no

\* remote controller type: NV-RCUTC-35HD