

Speed Dome IP Camera NVIP-2DN5020SD/IRH-2

5000
IP SERIES



KEY FEATURES



KEY FEATURES

- Resolution: 2 MPX
- Lens: motorized, auto-iris and auto-focus function,
- D/N function - IR cut filter
- Min. Illumination from 0.002 lx (0 lx, IR on)
- IR LED, range up to 100 m (depends on current optical zoom value)

COMPLIANCE



DIMENSIONS



IMAGE

Image Sensor	2 MPX CMOS sensor 1/2.8" SONY Exmor
Number of Effective Pixels	1920 (H) x 1080 (V)
Min. Illumination	0.02 lx/F1.2 - color mode • 0.002 lx/F1.2 - B/W mode • 0 lx (IR on) - B/W mode
S/N Ratio	> 50 dB (AGC off)
Electronic Shutter	auto/manual: 1/50 s ~ 1/10000 s
Digital Slow Shutter (DSS)	up to 1 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes

LENS

Optical Zoom	20x
Lens Type	motorized, auto-iris function, f=4.7 ~ 94 mm/F1.2 ~ F1.6
Auto-focus	continuous, zoom trigger, day/night mode trigger, manual trigger

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Visible Light Sensor	yes

NETWORK

Stream Resolution	1920 x 1080 (Full HD), 720 x 576 (D1), 640 x 480 (VGA), 640 x 360, 352 x 288 (CIF), 320 x 240 (QVGA)
Frame Rate	30 fps for each resolution
Multistreaming Mode	number of streams: 2
Video/Audio Compression	H.264, MJPEG/G.711, RAW_PCM
Number of Simultaneous Connections	max. 10
Bandwidth	18 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, UDP, DHCP, DDNS, NTP, RTSP, PPPoE, SMTP
ONVIF Protocol Support	Profile S (ONVIF 2.4)
Camera Configuration	from Internet Explorer browser • languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS

PTZ

Preset Commands	247
Tours	12 (up to 32 presets per tour)

Speed Dome IP Camera NVIP-2DN5020SD/IRH-2

Auto-Scans	12
Patterns	6 (max. 1000 commands or 3000 s in total for all patterns)
Tilt/Pan Range	0° ~ 98°/360° (continuous)
Pan/Tilt Speed	up to 180°/s (proportional to zoom)
Preset Speed	up to 90°/s

OTHER FUNCTIONS

Privacy Zones	8
Image Processing	180° image rotation, sharpening, mirror effect
System Reaction to Alarm Events	e-mail with attachment, alarm output activation, HTTP notification, PTZ

IR LED

LED Number	8
Range	up to 100 m (depends on current optical zoom value)
Angle	up to 45° (depends on current optical zoom value)

INTERFACES

Audio Input/Output	1 x RCA/1 x RCA
Alarm Input/Output	7 (NO/NC)/2 relay type yes 7 (NO/NC)/2 relay type (max. 12VDC/300mA)
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s

INSTALLATION PARAMETERS

Dimensions (mm)	205 (Φ) x 332 (H) with bracket: 205 (W) x 410 (H) x 270 (L)
Weight	4.3 kg with bracket: 4.7 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, In set: outdoor housing (integrated with the camera), wall mount bracket
Power Supply	24 VAC
Power Consumption	20 W • 32 W (IR illuminator on) • 40 W (IR and heater on)
Operating Temperature	-40°C ~ 60°C
Built-in Heater/Fan	yes/yes

To mount the camera may be necessary to use additional screws and nuts, not included in the adapter kit NVB-SD70PA & NVB-SD70CA