

Integrated access controller

KZ-1000-IP-M



The KZ-1000-IP controller has been designed for access control system and to be mounted on a wall without any additional enclosure. 32 bit processor ensures fast and reliable data processing. This is one door controller. With additional reader (also with keypad) it can use for two way control. It's possibility to set one from four identification mode: Card only (default mode); PIN only; Card or PIN; Card + PIN
KZ-1000-IP can work in standalone (programming from keypad) or in network mode. In network mode it can work on-line or off-line with supervisor KaDe Premium Plus software on PC.

Readers port quantity	1
Double-sided acces point	1
One-side acces point	1
Card buffer	20 000
Event buffer	50 000
Inputs - wire type / max. length	AWG #22 - 300 m
Lock output type	relay
Lock output monitoring	yes
Extension port	N.A.
Memory FLASH	no data
Memory SDRAM	no data
Auxiliary output power	12 V DC, 250mA
Doors	1
Readers port type	Wiegand 26
Communication port	TCP/IP, RS485
User identification mode	card, pin, card + pin, cart or pin
Card reading standard	MIFARE®
Frequency	13,56 MHz
Read range	2 - 5 cm
PIN length	6
Inputs	exit button, sensor door opening, PIR sensor
Outputs	lock, bell, alarm
Anti-Passback	only with PC
Interlock	no
Tamper	yes
Latch mode	yes
Supply power	12 VDC
Standby current	110mA
Weight	200 g
Humidity (non-condensing)	0% - 95%
Temperature range	2 to 55 °C



Integrated access controller **KZ-1000-IP-M**

Dimensions (mm)

150 x 88 x 25



AAT SYSTEMY BEZPIECZEŃSTWA sp. z o.o.

[GO TO THE WEBSITE](#)