

Bullet IP Camera with Motor-zoom Lens NVIP-8DN7560H/IRH-2P

7000 PRO
IP SERIES



KEY FEATURES



KEY FEATURES

- Resolution: 8 MPX (4K Ultra HD)
- Lens: motorized, auto-iris (P-Iris) and auto-focus function, $f=3.5 \sim 8$ mm/F1.45
- D/N function - IR cut filter
- microSD card support
- Min. Illumination from 0.005 lx (0 lx, IR on)
- IR LED, range up to 50 m

DIMENSIONS



IMAGE

Image Sensor	8 MPX CMOS sensor 1/1.7" SONY Exmor R STARVIS
Number of Effective Pixels	4152 (H) x 2174 (V)
Min. Illumination	0.05 lx/F1.45 - color mode (DSS) • 0.005 lx/F1.45 - B/W mode (DSS) • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/1 s ~ 1/10000 s
Digital Slow Shutter (DSS)	up to 1 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	3D

LENS

Lens Type	motorized, auto-iris (P-Iris) function, $f=3.5 \sim 8$ mm/F1.45
Auto-focus	zoom trigger, day/night mode trigger, manual trigger

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time, external, light sensor, smart
Switching Schedule	yes
Visible Light Sensor	yes

NETWORK

Stream Resolution	3840 x 2160 (4K Ultra HD), 3200 x 1800 (QHD+), 1920 x 1080 (Full HD), 1280 x 1024 (SXGA), 1280 x 720 (HD), 1024 x 768 (XGA), 800 x 600 (SVGA), 720 x 576 (D1), 640 x 480 (VGA), 352 x 288 (CIF), 320 x 240 (QVGA)
Frame Rate	30 fps for • 60 fps for and lower resolutions
Multistreaming Mode	number of streams: 4
Video/Audio Compression	H.264, MJPEG/G.711, G.726, AAC, LPCM
Number of Simultaneous Connections	max. 10
Bandwidth	70 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, Multicast, FTP, DHCP, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE
ONVIF Protocol Support	Profile S (ONVIF 2.6)
Camera Configuration	from Internet Explorer browser • languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS

OTHER FUNCTIONS

Privacy Zones	5
Motion Detection	yes

Bullet IP Camera with Motor-zoom Lens NVIP-8DN7560H/IRH-2P

Region of interest (ROI)	4
Audio Detection	
Image Processing	180° image rotation, sharpening, mirror effect, corridor mode
Prealarm/Postalarm	up to 3 s or 20 frames/up to 9999 s or 20 frames
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, saving file on NAS server, alarm output activation, HTTP notification

IR LED

LED Number	6
Range	50 m
Angle	60°

INTERFACES

Video Output	BNC, 1.0 Vp-p, 75 Ohm - maintenance only
Audio Input/Output	1 x Jack (3.5 mm)/1 x Jack (3.5 mm)
Alarm Input/Output	1 (NO/NC)/1
Network Interface	1 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s
Memory Card Slot	microSD - capacity up to 64GB

INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 90 (Φ) x 280 (L)
Weight	0.95 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included
Power Supply	12 VDC, 24 VAC, PoE (IEEE 802.3af, Class 3)
Power Consumption	7 W • 10 W (IR illuminator on) • 12 W (heater on) • 15 W (IR and heater on)
Operating Temperature	-40°C ~ 50°C
Humidity	max. 90%, relative (non-condensing)
Built-in Heater/Fan	yes/no