

Classic IP Starlight Camera with auto-back-focus function

NVIP-2DN7400C-1P

7000 PRO
IP SERIES



KEY FEATURES



- Resolution: 2 MPX
- D/N function - IR cut filter
- Auto-back-focus function
- microSD card support
- WDR with double scan sensor
- Min. Illumination from 0.0002 lx

DIMENSIONS



IMAGE

Image Sensor	2 MPX CMOS sensor 1/1.9" SONY Exmor
Number of Effective Pixels	1920 (H) x 1080 (V)
Min. Illumination	0.002 lx/F1.2 - color mode (DSS) • 0.0002 lx/F1.2 - B/W mode (DSS)
Electronic Shutter	auto/manual: 1/1 s ~ 1/10000 s
Digital Slow Shutter (DSS)	up to 1 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Image Stabilization (DIS)	yes
Digital Noise Reduction (DNR)	2D, 3D

LENS

Compatible Mount Type	CS
Iris Mode	D
Auto-back-focus	yes (function of the camera enables remote adjustment of focus of the image by automatically or manually change the position of the camera sensor relative to the lens)
Auto-focus	day/night mode trigger, manual trigger

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time, external, light sensor, smart
Switching Level Adjustment	yes
Switching Schedule	yes
Visible Light Sensor	yes

NETWORK

Stream Resolution	1920 x 1080 (Full HD), 1280 x 1024 (SXGA), 1280 x 720 (HD), 1024 x 768 (XGA), 800 x 600 (SVGA), 720 x 576 (D1), 640 x 480 (VGA), 352 x 288 (CIF), 176 x 144 (QCIF)
Frame Rate	60 fps for and lower resolutions
Multistreaming Mode	number of streams: 4
Video/Audio Compression	H.264, MJPEG/G.711, G.726
Number of Simultaneous Connections	max. 1
Bandwidth	6 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, Multicast, FTP, DHCP, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP
ONVIF Protocol Support	Profile S (ONVIF 2.6)
Camera Configuration	from Internet Explorer browser • languages: Polish, English, Russian, and others

Classic IP Starlight Camera with auto-back-focus function

NVIP-2DN7400C-1P

Compatible Software NOVUS MANAGEMENT SYSTEM VSS

VIDEO ANALYTICS

Functions face detection

OTHER FUNCTIONS

Privacy Zones 5

Motion Detection yes

Region of interest (ROI) 4

Audio Detection

Image Processing 180° image rotation, sharpening, mirror effect, corridor mode

Prealarm/Postalarm up to 3 s or 20 frames/up to 9999 s or 20 frames

System Reaction to Alarm Events e-mail, e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation, HTTP notification

INTERFACES

Video Output BNC, 1.0 Vp-p, 75 Ohm - maintenance only

Audio Input/Output 1 x Jack (3.5 mm)/1 x Jack (3.5 mm)

Alarm Input/Output 1 (NO/NC)/1

Network Interface 1 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s

Memory Card Slot microSD - capacity up to 32GB

INSTALLATION PARAMETERS

Dimensions (mm) 80 (W) x 53 (H) x 150 (L)

Weight 0.4 kg

Enclosure aluminium, white

Power Supply 12 VDC, PoE (IEEE 802.3af, Class 3)

Power Consumption 7.5 W

Operating Temperature -10°C ~ 50°C

Lens not included

Audio Detection and Face Detection functions available from firmware version nv20170718NSX