

Bullet IP Starlight Camera with Motor-zoom Lens

NVIP-2DN7460H/IRH-2P

7000 PRO
IP SERIES



KEY FEATURES



- Resolution: 2 MPX
- Lens: motorized, auto-iris and auto-focus function, f=3.3 ~ 8 mm/F1.5
- D/N function - IR cut filter
- microSD card support
- WDR with double scan sensor
- Min. Illumination from 0.0005 lx (0 lx, IR on)
- IR LED, range up to 40 m

COMPLIANCE



DIMENSIONS



IMAGE

| | |
|-----------------------------------|---|
| Image Sensor | 2 MPX CMOS sensor 1/1.9" SONY Exmor |
| Number of Effective Pixels | 1920 (H) x 1080 (V) |
| Min. Illumination | 0.01 lx/F1.5 - color mode (DSS) • 0.0005 lx/F1.5 - B/W mode (DSS) • 0 lx (IR on) - B/W mode |
| Electronic Shutter | auto/manual: 1/1 s ~ 1/10000 s |
| Digital Slow Shutter (DSS) | up to 1 s |
| Wide Dynamic Range (WDR) | yes (double scan sensor), 120dB |
| Digital Image Stabilization (DIS) | yes |
| Digital Noise Reduction (DNR) | 2D, 3D |

LENS

| | |
|------------|--|
| Lens Type | motorized, auto-iris function, f=3.3 ~ 8 mm/F1.5 |
| Auto-focus | zoom trigger, day/night mode trigger, manual trigger |

DAY/NIGHT

| | |
|----------------------------|---|
| Mode | day/night switching: mechanical IR cut filter |
| Switching Mode | auto, manual, time, external, light sensor, smart |
| Switching Level Adjustment | yes |
| Switching Schedule | yes |
| Visible Light Sensor | yes |

NETWORK

| | |
|------------------------------------|--|
| Stream Resolution | 1920 x 1080 (Full HD), 1280 x 1024 (SXGA), 1280 x 720 (HD), 1024 x 768 (XGA), 800 x 600 (SVGA), 720 x 576 (D1), 640 x 480 (VGA), 352 x 288 (CIF), 176 x 144 (QCIF) |
| Frame Rate | 60 fps for and lower resolutions |
| Multistreaming Mode | number of streams: 4 |
| Video/Audio Compression | H.264, MJPEG/G.711, G.726 |
| Number of Simultaneous Connections | max. 1 |
| Bandwidth | 6 Mb/s in total |
| Network Protocols Support | HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP |
| ONVIF Protocol Support | Profile S (ONVIF 2.6) |
| Camera Configuration | from Internet Explorer browser • languages: Polish, English, Russian, and others |
| Compatible Software | NOVUS MANAGEMENT SYSTEM VSS |

VIDEO ANALYTICS

| | |
|-----------|----------------|
| Functions | face detection |
|-----------|----------------|

OTHER FUNCTIONS

| | |
|---------------------------------|--|
| Privacy Zones | 5 |
| Motion Detection | yes |
| Region of interest (ROI) | 4 |
| Audio Detection | |
| Image Processing | 180° image rotation, sharpening, mirror effect, corridor mode |
| Prealarm/Postalarm | up to 3 s or 20 frames/up to 9999 s or 20 frames |
| System Reaction to Alarm Events | e-mail with attachment, saving file on FTP server, saving file on SD card, saving file on NAS server, alarm output activation, HTTP notification |

IR LED

| | |
|------------|------|
| LED Number | 6 |
| Range | 40 m |
| Angle | 60° |

INTERFACES

| | |
|--------------------|--|
| Video Output | BNC, 1.0 Vp-p, 75 Ohm - maintenance only |
| Audio Input/Output | 1 x Jack (3.5 mm)/1 x Jack (3.5 mm) |
| Alarm Input/Output | 1 (NO/NC)/1 |
| Network Interface | 1 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s |
| Memory Card Slot | microSD - capacity up to 32GB |

INSTALLATION PARAMETERS

| | |
|-----------------------|--|
| Dimensions (mm) | with bracket: 90 (Φ) x 280 (L) |
| Weight | 0.95 kg |
| Degree of Protection | IP 66 (details in the user's manual) |
| Enclosure | aluminium, white, fully cable managed wall mount bracket in-set included |
| Power Supply | 12 VDC/24 VAC, PoE (IEEE 802.3af, Class 3) |
| Power Consumption | 5.5 W • 9.5 W (IR illuminator on) • 7 W (heater on) |
| Operating Temperature | -40°C ~ 50°C |
| Built-in Heater/Fan | yes/no |

Audio Detection and Face Detection functions available from firmware version nv20170718NSX