Electric strike

KDA-STRIKE12SNT



Electric strike (NC), low-current, narrow, for remote wired opening of doors, gates, flaps, furniture. It can be used in steel, aluminum, wooden and PVC profiles, both internal and external, with the possibility of assembly for left and right doors as well as vertical and horizontal. Adjusting the hook in the range of 3mm facilitates assembly and ensures precise adjustment of the electric strike to the handle lock.

Possibility of assembly together with fixing plates:

KDA-BP130 - Flat plate, short, galvanized (130x25x3mm)

KDA-BP250 - Flat plate, long, galvanized (250x25x3mm)

KDA-BW130 - Flat plate, short with slip, made of stainless steel (130x25x3mm)

KDA-BW150 - Angular sheet, short, galvanized (130x25 / 32x3mm)

KDA-BKP250 - Angular, long, right, galvanized steel (250x25 / 32x3mm)

KDA-BKL250 - Angular plate, long, left, galvanized (250x25 / 32x3mm)

Explanation of the letters used in the symbols of electric strikes:
S- fail-secure
R- fail-safe
N- low-current
T- narrow
M- with microswitch
P- with memory
O- with unlock feature

Lock type	without supply normally close (NC)
power consumption	200 mA
Producer	KaDe
power	12V DC
dimensions	64 x 16.2 x 28
Maximal pressure on the electrocracker	300Kg
Additional functions	fail-secure, low-current, narrow