

# Monitor

## PM-32



### KEY FEATURES

- LED backlight
- Function preventing from burning-in static images on the LCD panel

### LCD PANEL

|                        |                       |
|------------------------|-----------------------|
| Panel Type             | IPS, LED backlight    |
| Screen Size (Diagonal) | 31.5"                 |
| Panel Resolution       | 1920 x 1080           |
| Format                 | 16:9                  |
| Brightness             | 350 cd/m <sup>2</sup> |
| Contrast Ratio         | 1400:1                |
| Viewing Angle (H/V)    | 178°/178°             |
| Response Time          | 4 ms                  |
| Display Color          | 16.7 mln              |

### OTHER FUNCTIONS

|                   |   |
|-------------------|---|
| OSD               | languages: Polish, English, Russian, others |
| Digital Filter    | 3D  |
| Built-in Speakers | 2 x 10 W                                    |

### INTERFACES

|                    |  |
|--------------------|--|
| Video Input        | 1 x VGA, 1 x HDMI, 1 x DVI                   |
| Audio Input        | 1 x Mini Jack stereo, 2 x RCA (loop-through) |
| External Control   | LAN RJ-45, RS-232 2.5mm Jack, IR IN/OUT      |
| Other Connectivity | USB 2.0                                      |

### INSTALLATION PARAMETERS

|                       |                                       |
|-----------------------|---------------------------------------|
| Dimensions (mm)       | 727 (W) x 425 (H) x 64 (D)            |
| Weight                | 5.2 kg                                |
| Case                  | black, metal                          |
| Power Supply          | 100 ~ 240 VAC                         |
| Power Consumption     | 81 W (max)                            |
| Operating Temperature | 0°C ~ 40°C                            |
| Mounting Standard     | VESA 200 x 200 mm • VESA 100 x 100 mm |