

IP Recorder

NVR-6316-H1



KEY FEATURES



•16 x video and audio channels

•Recording speed up to 480 fps at 3840 x 2160

- •Supports resolution up to 3840 x 2160 •Recorded stream size: 80 Mb/s in total from all
- cameras

•1 x internal place for HDD mounting

•1 x monitor outputs (HDMI 4K UltraHD) •Intelligent image analysis

DIMENSIONS



IP Cameras	up to 16 channels at 3840 x 2160 resolution (video + audio)
Maximum Supported Camera Resolution	3840 x 2160
Compression	H.264, H.264+, H.265
Monitor Output	main (split screen, full screen, sequence): $1 \times HDMI$ (4K UltraHD) , VGA (up to 1 monitor simultaneously)**
Dualstreaming Support	yes
AUDIO	
Audio Input/Output	- / 1 x line-out (RCA)
RECORDING	
Stream Size	80 Mb/s in total from all cameras
Recording Mode	continuous, triggered by: manual, motion detection
Prealarm/Postalarm	up to 5 s/up to 600 s
DISPLAY	
Display Speed	480 fps (16 x 30 fps)
PLAYBACK	
Playback Speed	480 fps (16 x 30 fps)
Recorded Data Search	by date/time, events
BACKUP	
Backup Methods	USB port (HDD or Flash memory), network
Backup File Format	AVI, RPAS (player included)
STORAGE	
Internal Storage	available mount: 1 x HDD 3.5" 10 TB SATA
Total Internal Capacity	10 ТВ
ALARM	
Internal Alarm Input/Output	4/1 relay type (max. 12VDC/1A)
Camera Alarm Input/Output	supports IP camera's alarm input/output
Motion Detection	supports camera's motion detection
System Reaction to Alarm Events	buzzer, recording activation, PTZ, e-mail with atatchment

NoVus'

Supported Functions

Exception, Scene Change, Video Blurred, Video Color Cast, Tripwire, Zone entrance, Abandoned Object, Object Disappearance





IP Recorder NVR-6316-H1

NETWORK

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Network Protocols Support	HTTP, TCP/IP, IPv4, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnF SNMP, SMTP
Mobile applications	SuperLive Plus (iPhone, Android)
Number of Simultaneous Connectio	nsup to 5 clients, up to 20 main streams or 64 substreams or 16 playback streams in total
Bandwidth	80 Mb/s in total to all client workstations
PTZ	
PTZ Functions	pan/tilt/zoom, preset commands
AUXILIARY INTERFACES	
USB Ports	2 x USB 2.0
OPERATING SYSTEM	
Operating System	Linux
Operation Mode	triplex
OSD	languages: Polish, English, others
Control	PC mouse and IR remote controller (in-set included), network
System Diagnostic	automatic control of: HDDs, network, camera connection loss
Security	password protection, IP filtering, MAC filtering
INSTALLATION PARAMETERS	
Dimensions (mm)	300 (W) x 52 (H) x 248 (D)
Weight	1.5 kg (without HDD)
Power Supply	12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)
Power Consumption	20 W (with 1 HDD)
Operating Temperature	-10°C ~ 50°C

Additional 8T disk mounting holes are available from the NVR6316H1170629xxxx serial number Support for intelligent image analysis works only with NOVUS IP 6000 & 3000 series cameras The availability of the following functions: double-stream operation, motion detection, alarm inputs / outputs, PTZ control depends on the functionality of the camera and the capabilities of the communication protocol. Detailed data can be found in the compatibility table available in the DOWNLOADS tab. ** VGA monitor output available via added HDMI -> VGA adapter

