

IP Recorder

NVR-6308P8-H1**6000** VSS IP**KEY FEATURES**

- 8 x PoE Ethernet ports
- 8 x video and audio channels
- Recording speed up to 240 fps at 3840 x 2160
- Supports resolution up to 3840 x 2160
- Recorded stream size: 50 Mb/s in total from all cameras
- 1 x internal place for HDD mounting
- 2 x monitor outputs (HDMI 4K UltraHD, VGA)
- Intelligent image analysis

DIMENSIONS**VIDEO**

Maximum Supported Camera Resolution	3840 x 2160
Compression	H.264, H.264+, H.265
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI (4K UltraHD), 1 x VGA (up to 2 monitors simultaneously)
Dualstreaming Support	yes*

AUDIO

Audio Input/Output	- / 1 x line-out (RCA)
--------------------	------------------------

RECORDING

Stream Size	50 Mb/s in total from all cameras
Recording Mode	continuous, triggered by: manual, motion detection
Prealarm/Postalarm	up to 5 s/up to 600 s

DISPLAY

Display Speed	240 fps (8 x 30 fps)*
---------------	-----------------------

PLAYBACK

Playback Speed	240 fps (8 x 30 fps for 3840 x 2160) *
Recorded Data Search	by date/time, events

BACKUP

Backup Methods	USB port (HDD or Flash memory), network
Backup File Format	AVI

STORAGE

Internal Storage	available mount: 1 x HDD 3.5" 10 TB SATA
Total Internal Capacity	10 TB

ALARM

Camera Alarm Input/Output	supports IP camera's alarm input/output
Motion Detection	supports camera's motion detection
System Reaction to Alarm Events	buzzer, recording activation, PTZ, e-mail with attachment

INTELLIGENT IMAGE ANALYSIS

Supported Functions	Exception, Scene Change, Video Blurred, Video Color Cast, Tripwire, Zone entrance, Abandoned Object, Object Disappearance
---------------------	---

NETWORK

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s • 8 x Ethernet PoE (IEEE802.3af, Class 3) - RJ-45 interface, 10/100 Mbit/s
-------------------	--



IP Recorder NVR-6308P8-H1

Network Protocols Support HTTP, TCP/IP, IPv4, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SNMP, SMTP

ONVIF Protocol Support S profile (ONVIF 2.2 or higher)

PC/MAC Software NMS, Internet Explorer, NVR-6000 Viewer/NVR-6000 Viewer

Mobile applications SuperLive Plus (iPhone, Android)

Number of Simultaneous Connections up to 2 clients

Bandwidth 50 Mb/s in total to all client workstations

PTZ

PTZ Functions pan/tilt/zoom, preset commands*

AUXILIARY INTERFACES

USB Ports 2 x USB 2.0

OPERATING SYSTEM

Operating System Linux

Operation Mode triplex

OSD languages: Polish, English, others

Control PC mouse and IR remote controller (in-set included), network

System Diagnostic automatic control of: HDDs, network, camera connection loss

Security password protection, IP filtering, MAC filtering

INSTALLATION PARAMETERS

Dimensions (mm) 300 (W) x 52 (H) x 248 (D)

Weight 1.16 kg (without HDD)

Power Supply 100 ~ 240 VAC

Power Consumption 20 W (with 1 HDD) + 100 W PoE

Operating Temperature -10°C ~ 50°C

Additional 8T disk mounting holes are available from the NVR6308P8H1170620xxxx serial number

Support for intelligent image analysis works only with NOVUS IP 3000 series cameras

** Available with dual streaming mode.*

