

Vandal Proof AHD Multistandard Camera with Fisheye Lens

NVAHD-2DN5103MV/IR-1

5000
AHD SERIES

KEY FEATURES



- D/N function - IR cut filter
- resolution 1080p
- Lens: "fisheye", $f=1.6\text{ mm}/F1.4$
- Smart IR function
- multistandard: AHD, CVI, TVI, 960H
- Min. Illumination from 0.0001 lx
- IR LED, range up to 5 m

DIMENSIONS



IMAGE

Image Sensor	CMOS sensor 1/2.9" SONY
Operating mode	AHD 1080p, TVI 1080p, CVI 1080p, analog 960H
Number of Effective Pixels	1920 (H) x 1080 (V)
Resolution	1080p
Min. Illumination	0.1 lx/F1.4 - color mode • 0.05 lx/F1.4 - B/W mode • 0.005 lx/F1.4 - color mode (DSS) • 0.0001 lx/F1.4 - B/W mode (DSS) • 0 lx (IR on) - B/W mode
S/N Ratio	> 52 dB (AGC off)
Electronic Shutter	auto/manual: 1/25 s ~ 1/50000 s (AHD), , 1/25 s ~ 1/50000 s (analog 960H)
Digital Slow Shutter (DSS)	up to 30x
High Light Compensation (HLC)	yes
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes

LENS

Lens Type	fisheye, $f=1.6\text{ mm}/F1.4$
-----------	---------------------------------

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual
Switching Level Adjustment	yes
Switching Delay	0 ~ 60 s
Visible Light Sensor	yes

OTHER FUNCTIONS

System	PAL, NTSC
OSD	languages: Polish, English, Russian, others
Privacy Zones	4
Motion Detection	yes
Image Processing	180° image rotation, sharpening, mirror effect
Remote control	Yes (COAX protocol)

IR LED

LED Number	4
Range	5 m
Angle	120°

Vandal Proof AHD Multistandard Camera with Fisheye Lens **NVAHD-2DN5103MV/IR-1**

INTERFACES

Video Output	BNC, 1.0 Vp-p, 75 Ohm
--------------	-----------------------

INSTALLATION PARAMETERS

Dimensions (mm)	135 (Φ) x 49 (H)
Weight	0.43 kg
Degree of Protection	IP 55 (details in the user's manual)
Enclosure	vandalproof, aluminium, white
Power Supply	12 VDC
Power Consumption	1 W • 6 W (IR illuminator on)
Operating Temperature	-30°C ~ 40°C