

Classic AHD Multistandard Camera

NVAHD-2DN5100MC-3



KEY FEATURES



- D/N function - IR cut filter
- resolution 1080p
- multistandard: AHD, CVI, TVI, 960H
- Min. Illumination from 0.0001 lx

DIMENSIONS



IMAGE

Image Sensor	CMOS sensor 1/2.9" SONY
Operating mode	AHD 1080p, TVI 1080p, CVI 1080p, analog 960H
Number of Effective Pixels	1920 (H) x 1080 (V)
Resolution	1080p
Min. Illumination	0.1 lx/F1.4 - color mode • 0.05 lx/F1.4 - B/W mode • 0.005 lx/F1.4 - color mode (DSS) • 0.0001 lx/F1.4 - B/W mode (DSS)
S/N Ratio	> 52 dB (AGC off)
Electronic Shutter	auto/manual: 1/25 s ~ 1/50000 s (AHD), , 1/50 s ~ 1/50000 s (analog 960H)
Digital Slow Shutter (DSS)	up to 30x
High Light Compensation (HLC)	yes
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes

LENS

Compatible Mount Type	C, CS
Iris Mode	D

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual
Switching Level Adjustment	yes
Switching Delay	0 ~ 60 s

OTHER FUNCTIONS

OSD	languages: Polish, English, Russian, others
Privacy Zones	4
Motion Detection	yes
Image Processing	180° image rotation, sharpening, mirror effect
Remote control	Yes (COAX protocol)

INTERFACES

Video Output	BNC, 1.0 Vp-p, 75 Ohm
--------------	-----------------------

INSTALLATION PARAMETERS

Dimensions (mm)	58 (W) x 62 (H) x 125 (L)
Weight	0.39 kg



Classic AHD Multistandard Camera **NVAHD-2DN5100MC-3**

Enclosure	aluminium, white
Power Supply	100 ~ 230 VAC
Power Consumption	2.3 W
Operating Temperature	-30°C ~ 40°C

** Remote controller type: NV-RCUTC-35HD / Lens not included*

