

Bullet IP Camera with Motor-zoom Lens

NVIP-5DN2004H/IR-1P

4000 VSS IP



KEY FEATURES



- Resolution: 5 MPX
- Lens: motorized, auto-focus function, $f=2.8 \sim 12$ mm/F1.4
- D/N function - IR cut filter
- Video content analysis
- Min. Illumination: 0.07 lx (0 lx, IR on)
- IR LED, range up to 40 m

COMPLIANCE



DIMENSIONS



IMAGE

Image Sensor	5 MPX CMOS sensor 1/3.2" OmniVision
Number of Effective Pixels	2592 (H) x 1944 (V)
Min. Illumination	0.07 lx/F1.4 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/5 s ~ 1/20000 s
Digital Slow Shutter (DSS)	up to 1/5 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes

LENS

Lens Type	motorized, $f=2.8 \sim 12$ mm/F1.4
Auto-focus	zoom trigger, day/night mode trigger, manual trigger

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual
Switching Delay	1 ~ 36 s
Visible Light Sensor	yes

NETWORK

Stream Resolution	2592 x 1520, 2592 x 1944, 2304 x 1296, 1920 x 1080 (Full HD), 2048 x 1520, 1280 x 960, 1280 x 720 (HD), 704 x 576, 640 x 480 (VGA), 320 x 240 (QVGA)
Frame Rate	15 fps for • 20 fps for • 30 fps for and lower resolutions
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.265/-
Number of Simultaneous Connections	max. 10
Bandwidth	63 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SMTP
ONVIF Protocol Support	Profile S (ONVIF 2.6)
Camera Configuration	from Internet Explorer, Firefox browser • languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS

VIDEO ANALYTICS

Functions	tamper, abandoned object, object disappearance, line cross, zone entrance, object counting, face detection, pedestrian detection
-----------	--

Bullet IP Camera with Motor-zoom Lens NVIP-5DN2004H/IR-1P

OTHER FUNCTIONS

Privacy Zones	4
Motion Detection	yes
Region of interest (ROI)	8
Image Processing	180° image rotation, corridor mode, vertical flip, horizontal flip
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server

IR LED

LED Number	30
Range	40 m
Angle	120°

INTERFACES

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
-------------------	---

INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 84 (Φ) x 232 (L)
Weight	0.7 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Power Consumption	2 W • 8 W (IR illuminator on)
Operating Temperature	-35°C ~ 60°C