

Integrated access controller

KDH-KZ2000-IP-M



The KDH-KZ2000-IP-U_M controller has been designed for access control system and to be mounted on a wall without any additional enclosure. 32 bit processor ensures fast and reliable data processing. This is one door controller. With additional reader (also with keypad) it can use for two way control. It's possibility to set one from four identification mode: Card only (default mode); PIN only; Card or PIN; Card + PIN

KDH-KZ2000-IP-U_M can work in standalone (programming from keypad) or in network mode. In network mode it can work on-line or off-line with supervisor KaDe Premium Plus software II on PC.

Readers port quantity	1
Double-sided acces point	1
One-side acces point	1
Card buffer	20 000
Event buffer	50 000
Lock output type	relay
Doors	1
Readers port type	Wiegand 34 bit
Communication port	TCP/IP
User identification mode	card, pin, card + pin, cart or pin
Card reading standard	MIFARE®
Frequency	13,56 MHz
Read range	2 - 5 cm
PIN length	6
Inputs	exit button, sensor door opening, PIR sensor
Outputs	lock, bell, alarm
Anti-Passback	only with PC
Interlock	no
Tamper	yes
Latch mode	yes
Supply power	12 VDC
Standby current	110mA
Humidity (non-condensing)	0% - 95%
Temperature range	2 to 55 °C
Dimensions (mm)	122 x 78 x 30