

Bullet AHD Multistandard Camera NVAHD-2DN5106MH/IR-1

5000
AHD SERIES



KEY FEATURES



- D/N function - IR cut filter
- resolution 1080p
- Lens: varifocal, f=2.8 ~ 12 mm/F1.4
- multistandard: AHD, CVI, TVI, 960H
- Min. Illumination from 0.0001 lx (0 lx, IR on)
- IR LED, range up to 35 m

DIMENSIONS



IMAGE

| | |
|-------------------------------|---|
| Image Sensor | CMOS sensor 1/2.9" SONY |
| Operating mode | AHD 1080p, TVI 1080p, CVI 1080p, analog 960H |
| Number of Effective Pixels | 1920 (H) x 1080 (V) |
| Resolution | 1080p |
| Min. Illumination | 0.1 lx/F1.4 - color mode • 0.05 lx/F1.4 - B/W mode • 0.005 lx/F1.4 - color mode (DSS) • 0.0001 lx/F1.4 - B/W mode (DSS) • 0 lx (IR on) - B/W mode |
| S/N Ratio | > 52 dB (AGC off) |
| Electronic Shutter | auto/manual: 1/25 s ~ 1/50000 s |
| Digital Slow Shutter (DSS) | up to 30x |
| High Light Compensation (HLC) | yes |
| Wide Dynamic Range (WDR) | yes |
| Digital Noise Reduction (DNR) | 2D, 3D |
| Defog Function (F-DNR) | yes |

LENS

| | |
|-----------|-------------------------------|
| Lens Type | varifocal, f=2.8 ~ 12 mm/F1.4 |
|-----------|-------------------------------|

DAY/NIGHT

| | |
|----------------------------|---|
| Mode | day/night switching: mechanical IR cut filter |
| Switching Mode | auto, manual |
| Switching Level Adjustment | yes |
| Switching Delay | 0 ~ 60 s |
| Visible Light Sensor | yes |

OTHER FUNCTIONS

| | |
|------------------|---|
| OSD | languages: Polish, English, Russian, others (joystick on the cable) |
| Privacy Zones | 4 |
| Motion Detection | yes |
| Image Processing | 180° image rotation, sharpening, mirror effect |
| Remote control | Yes (COAX protocol) |

IR LED

| | |
|------------|------|
| LED Number | 30 |
| Range | 35 m |
| Angle | 120° |

INTERFACES

Bullet AHD Multistandard Camera NVAHD-2DN5106MH/IR-1

Video Output BNC, 1.0 Vp-p, 75 Ohm

INSTALLATION PARAMETERS

| | |
|-----------------------|--|
| Dimensions (mm) | with bracket: 84 (Φ) x 270 (L) |
| Weight | 0.7 kg |
| Degree of Protection | IP 66 (details in the user's manual) |
| Enclosure | aluminium, white, fully cable managed wall mount bracket in-set included |
| Power Supply | 12 VDC |
| Power Consumption | 1.2 W • 5 W (IR illuminator on) |
| Operating Temperature | -30°C ~ 40°C |

** Note: UTC functionality available on cameras with serial numbers starting from: 150611xxxx
Remote controller type: NV-RCUTC-35HD*