

Bullet IP Camera with Motor-zoom Lens

NVIP-8DN3512H/IR-1P

6000 VSS IP



KEY FEATURES



- Resolution: 8 MPX (4K Ultra HD)
- Lens: motorized, auto-focus function, $f=3.3 \sim 12$ mm/F1.4
- D/N function - IR cut filter
- Video content analysis
- microSD card support
- Min. Illumination: 0.01 lx (0 lx, IR on)
- IR LED, range up to 50 m

DIMENSIONS



IMAGE

Image Sensor	8 MPX CMOS sensor 1/2.5" SONY Exmor R STARVIS
Number of Effective Pixels	3840 (H) x 2160 (V)
Min. Illumination	0.01 lx/F1.4 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto: 1/25 s ~ 1/100000 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes

LENS

Lens Type	motorized, $f=3.3 \sim 12$ mm/F1.4
Auto-focus	zoom trigger, day/night mode trigger, manual trigger

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time, light sensor
Switching Level Adjustment	yes
Switching Schedule	yes
Visible Light Sensor	yes

NETWORK

Stream Resolution	3840 x 2160 (4K Ultra HD), 1920 x 1080 (Full HD), 1280 x 720 (HD), 720 x 576 (D1), 352 x 288 (CIF)
Frame Rate	30 fps for and lower resolutions
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.265, MJPEG/G.711
Number of Simultaneous Connections	max. 4
Bandwidth	50 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, UDP, FTP, DHCP, DDNS, NTP, RTSP, PPPoE, SMTP
ONVIF Protocol Support	Profile S (ONVIF 2.3)
Camera Configuration	from Internet Explorer, Firefox, Chrome, Opera browser • languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS

VIDEO ANALYTICS

Functions	tamper, abandoned object, object disappearance, line cross, zone entrance, scene change, video blurred, video color cast
-----------	--

Bullet IP Camera with Motor-zoom Lens NVIP-8DN3512H/IR-1P

OTHER FUNCTIONS

Privacy Zones	4
Motion Detection	yes
Region of interest (ROI)	8
Image Processing	90° image rotation, 180° image rotation, sharpening, mirror effect
Prealarm/Postalarm	-/up to 120 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation

IR LED

LED Number	48
Range	50 m
Angle	90°

INTERFACES

Video Output	BNC, 1.0 Vp-p, 75 Ohm - maintenance only
Audio Input/Output	1 x Jack (3.5 mm)/1 x Jack (3.5 mm)
Alarm Input/Output	1 (NO/NC)/1
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 128GB

INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 109 (Φ) x 284 (L)
Weight	1.10 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, wall mount bracket in-set included , IK10 impact rating
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Power Consumption	4.5 W • 8 W (IR illuminator on)
Operating Temperature	-20°C ~ 50°C

Settings for stream 60 FPS @ 1080p are available from firmware 3.4.3(2016-8-17) up.