

Bullet AHD Multistandard Camera

NVAHD-2DN5101MH/IR-1

5000
AHD SERIES



KEY FEATURES



- D/N function - IR cut filter
- resolution 1080p
- Lens: fixed focal, $f=3.6$ mm/F1.9
- multistandard: AHD, CVI, TVI, 960H
- Min. Illumination from 0.0005 lx (0 lx, IR on)
- IR LED, range up to 15 m

DIMENSIONS



IMAGE

Image Sensor	CMOS sensor 1/2.9" SONY
Operating mode	AHD 1080p, TVI 1080p, CVI 1080p, analog 960H
Number of Effective Pixels	1985 (H) x 1105 (V)
Resolution	1080p
Min. Illumination	0.5 lx/F1.9 - color mode • 0.05 lx/F1.9 - B/W mode • 0.005 lx/F1.9 - color mode (DSS) • 0.0005 lx/F1.9 - B/W mode (DSS) • 0 lx (IR on) - B/W mode
S/N Ratio	> 52 dB (AGC off)
Electronic Shutter	auto/manual: 1/25 s ~ 1/50000 s
Digital Slow Shutter (DSS)	up to 30x
High Light Compensation (HLC)	yes
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes

LENS

Lens Type	fixed focal, $f=3.6$ mm/F1.9
-----------	------------------------------

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual
Switching Delay	0 ~ 60 s
Visible Light Sensor	yes

OTHER FUNCTIONS

OSD	languages: Polish, English, Russian, others (joystick on the cable)
Privacy Zones	4
Motion Detection	yes
Image Processing	Defective Pixel Correction (DPC), 180° image rotation, sharpening, mirror effect, picture-freeze
Remote control	Yes (COAX protocol)

IR LED

LED Number	24
Range	15 m
Angle	80°

INTERFACES

Bullet AHD Multistandard Camera NVAHD-2DN5101MH/IR-1

Video Output BNC, 1.0 Vp-p, 75 Ohm

INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 70 (Φ) x 173 (L)
Weight	0.4 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included
Power Supply	12 VDC
Power Consumption	1 W • 4 W (IR illuminator on)
Operating Temperature	-30°C ~ 40°C