NOVUS

IP Recorder

NVR-7732-H8





KEY FEATURES













•32 x video and audio channels







- \bullet Recording speed up to 960 fps at 3840 x 2160
- \bullet Supports resolution up to 3840 x 2160
- •Recorded stream size: 320 Mb/s in total from all cameras
- •8 x internal place for HDD mounting
- •5 x monitor outputs (HDMI 4K UltraHD, HDMI, VGA,
- •RACK mount
- •ipGO extremely easy adding and configuring IP cameras with DVR menu
- •RAID protects recordings

COMPLIANCE





DIMENSIONS









VIDEO	
Maximum Supported Camera Resolution	3840 x 2160
Compression	H.264, H.264+, H.265
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI (4K UltraHD), 1 x VGA, 1 x BNC (up to 3 monitors simultaneously) • spot: 1 x HDMI (FullHD),1 x VGA
Dualstreaming Support	yes*
AUDIO	
Audio Input/Output	- / 1 x line-out (RCA)
RECORDING	
Recording Speed	960 fps (32 x 30 fps for 1280 x 720) • 960 fps (32 x 30 fps for 1920 x 1080) • 960 fps (32 x 30 fps for 2048 x 1536) • 960 fps (32 x 30 fps for 2560 x 1440)
Stream Size	320 Mb/s in total from all cameras
Recording Mode	continuous, triggered by: manual, alarm input, motion detection

Recording Mode continuous, triggered by: manual, alarm input, motion detection Schedule individual settings for: each camera, each day of the week, configuration with an accuracy of: 15 min, possibility of combining individual recording modes

Prealarm/Postalarm up to 30 s/up to 180 s

DISPLAY

960 fps (32 x 30 fps)** Display Speed

PLAYBACK

480 fps (16 x 30 fps for 1280 x 720) ** • 480 fps (16 x 30 fps for 1920
x 1080) ** • 480 fps (16 x 30 fps for 2048 x 1536) ** • 480 fps (16 x
30 fps for 2560 x 1440) ** • 480 fps (16 x 30 fps for 3840 x 2160) **
30 lp3 lol 2300 x 1440) 400 lp3 (10 x 30 lp3 lol 3

Recorded Data Search by date/time, events

BACKUP

Backup Methods	USB port (HDD or Flash memory), network, eSATA port (HDD)
Backup File Format	AVI, DAT

STORAGE

Internal Storage	available mount: 8 x HDD 3.5" 8 TB SATA
Total Internal Capacity	64 TB

ΛΙΛΡΜ

APANCI.	
Internal Alarm Input/Output	16/4 relay type (max. 12VDC/1A)
Motion Detection	supports camera's motion detection*





IP Recorder NVR-7732-H8

System Reaction to Alarm Events	buzzer, alarm output activation, recording activation, PTZ, e-mail with atatchment
NETWORK	
Network Interface	2 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s
Network Protocols Support	HTTP, TCP/IP, IPv4, UDP, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SMTP
PC/MAC Software	NMS, Internet Explorer, Firefox, Chrome, Opera/Safari
Mobile applications	RealViewPro (iPhone, Android)
Number of Simultaneous Connection	nsup to 2 clients
Bandwidth	320 Mb/s in total to all client workstations
PTZ	
PTZ Functions	pan/tilt/zoom, preset commands*
AUXILIARY INTERFACES	
USB Ports	3 x USB 2.0, 1 x USB 3.0
OPERATING SYSTEM	
Operating System	Linux
Operation Mode	triplex
OSD	languages: Polish, English, others
Control	PC mouse (in-set included), network
System Diagnostic	automatic control of: HDDs, network, camera connection loss
Security	password protection, IP filtering, MAC filtering
INSTALLATION PARAMETERS	
Dimensions (mm)	440 (W) x 89 (H) x 460 (D)
Weight	8.7 kg
Power Supply	100 ~ 240 VAC
Power Consumption	175 W (with 8 HDDs)

 $[*] Function \ depends \ on \ communication \ protocol, \ for \ details \ please \ check \ compatibility \ table \ in \ section \ DOWNLOADABLE \ FILES.$





^{**} Available with dual streaming mode.

^{***} List of compatible HDD models and maximum of their capacities is available in section DOWNLOADABLE FILES.