4-port PoE Switch


NVS-3004SP



KEY FEATURES

- 4 x 100Mbps PoE+
- 1 x 100Mb/s UPLINK

DIMENSIONS



GENERAL

Device Type	PoE+ Switch

NETWORK

Ports	PoE+ Ports: 4 x 10/100Mbps (the number of ports simultaneously operating with PoE + mode is limited by PoE budget) • UPLINK ports: 1 x 10/100Mbps
PoE standards	IEEE802.3af, Class 3, IEEE802.3at, Class 4
PoE mode	Endspan (1,2+ / 3,6-), Midspan (4,5+ / 7,8-)
Switching capacity	1 Gb/s
Supported protocols	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3x
MAC address list	1K

FUNCTIONS

CCTV	Extend mode switch that increases transmission range and PoE up to 150 - 250m (Using 10 Mb/s bandwidth)
Additional operating modes	Extend
Surge protection	yes

INSTALLATION PARAMETERS

Case	Metal, navy blue color
Dimensions (mm)	100 (W) x 26 (H) x 100 (L)
Weight	225 kg
Input Voltage	51 VDC (power supply 100 ~ 240 VAC/51 VDC included)
Power Consumption	63 W
PoE Budget	63 W for ports 1 to 4, up to 30 W for one port
Operating Temperature	0°C ~ 40°C

Maximum ranges depend on cable quality, interference and camera model. The ranges were determined in laboratory conditions. For information on the exact ranges for a given camera connection and switches please contact support or perform tests in the real environment of the future operation of the devices.

AAT SYSTEMY BEZPIECZEŃSTWA sp. z o.o.

GO TO THE WEBSITE