NoVus

4-port PoE Switch

NVS-3004SP




KEY FEATURES

- •4 x 100Mb/s PoE+
- •1 x 100Mb/s UPLINK

DIMENSIONS







GENERAL

Device Type	PoE+ Switch
NETWORK	
Ports	PoE+ Ports: 4 x 10Mb/s / 100Mb/s (the number of ports simultaneously operating with PoE + mode is limited by PoE budget) • UPLINK ports: 1 x 10Mb/s / 100Mb/s
PoE standards	IEEE802.3af, Class 3, IEEE802.3at, Class 4
PoE modes	Endspan (1,2+ / 3,6-), Midspan (4,5+ / 7,8-)
Switching capacity	1 Gb/s
Protocols Support	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3x
MAC ADDRESS list	1K
FUNCTIONS	
ССТУ	Extended mode switch that increases transmission range and PoE up to 150 - 250m (Using 10 Mb/s bandwidth)
Additional operating modes	Extended
Surge protection	yes

INSTALLATION PARAMETERS

Case	Metal, color navy blue
Dimensions (mm)	100 (W) x 26 (H) x 100 (L)
Weight	225 g
Input Voltage	51 VDC (power supply 100 ~ 240 VAC/51 VDC included)
Power Consumption	63 W (maximum)
PoE Budget	63 W for ports 1 to 4, up to 30 W for one port
Operating Temperature	0°C ~ 40°C

Maximum ranges depend on cable quality, interference and camera model. The ranges were determined in laboratory conditions. For information on the exact ranges for a given camera connection and switches please contact support or perform tests in the real environment of the future operation of the devices.



