

Bullet Camera

NVC-401H/IR

**400
SERIES**



KEY FEATURES

960H



- D/N function - electronic
- Resolution: 650 TVL
- Lens: fixed focal, f=3.6 mm/F2.0
- IR LED, range up to 15 m
- Smart IR function
- Extended IR LED life
- Min. Illumination: 0.14 lx (0 lx, IR on)

DIMENSIONS



IMAGE

Image Sensor	CCD sensor 1/3" SONY Super HAD II
Number of Effective Pixels	976 (H) x 582 (V)
Horizontal Resolution	650 TVL - color mode, 650 TVL - B/W mode
Min. Illumination	0.14 lx/F2.0 - color mode • 0 lx (IR on) - B/W mode
S/N Ratio	> 52 dB (AGC off)
Electronic Shutter	auto: 1/50 s ~ 1/100000 s
High Light Compensation (HLC)	yes
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D
Defog Function (F-DNR)	no

LENS

Lens Type	fixed focal, f=3.6 mm/F2.0
-----------	----------------------------

DAY/NIGHT

Mode	electronic D/N function
Switching Mode	auto, manual
Switching Level Adjustment	yes
Switching Delay	0 ~ 255 s
Visible Light Sensor	yes

OTHER FUNCTIONS

OSD	languages: English, Russian, others (joystick on the cable)
Privacy Zones	4
Motion Detection	yes
Image Processing	mirror effect

IR LED

LED Number	24
Range	15 m
Angle	80°

INTERFACES

Video Output	BNC, 1.0 Vp-p, 75 Ohm
--------------	-----------------------

INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 66 (W) x 67 (H) x 175 (L)
Weight	0.59 kg

**Bullet Camera
NVC-401H/IR**

Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, ivory, fully cable managed wall mount bracket in-set included
Power Supply	12 VDC
Power Consumption	1.2 W • 3.1 W (IR illuminator on)
Operating Temperature	-30°C ~ 40°C