NoVus

8-PORT POE+ SWITCH NV-108S/P+



KEY FEATURES

•8 x 100Mbps PoE+

GENERAL

Device Type	PoE+ Switch
NETWORK	
Ports	PoE+ Ports: $8 \times 10/100 \text{Mbps}$ (the number of ports simultaneously operating with PoE+ mode is limited by PoE budget) • UPLINK ports: $1 \times 10/100/1000 \text{Mbps}$ • Optical UPLINK ports: $1 \times \text{SFP}$
Transmission Distance	1-8 ports in PoE mode: 150 m * • 1-8 ports in PoE+ mode: 20 m * • UPLINK port: 100 m *
PoE standards	IEEE802.3af, Class 3, IEEE802.3at, Class 4
Protocols Support	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T, IEEE 802.3z 1000BASE-SX\LX
Packet buffer	1 MB
MAC address list	8K
FUNCTIONS	
Buttons	8 reset buttons, one for each interface, 1 button to device reset
Surge protection	yes

Case	Aluminium, color black
Dimensions (mm)	159 (W) x 46.5 (H) x 110 (L)
Weight	570 kg
Input Voltage	48 VDC - 57 VDC (power supply 100 \sim 240 VAC/48 VDC Included)
Power Consumption	5 W (maximum)
PoE Budget	110 W for ports 1 to 8, up to 30 W for one port
Operating Temperature	-10°C ~ 55°C

 $^{^{}st}$ The values was achieved in a test environment. In different environment this value can change due to interferences or influence of other devices.



^{•1} x 1000Mb/s UPLINK, 1 x 1000Mb/s SFP UPLINK