NoVus

Digital Video Recorder

NDR-BA3104-II





KEY FEATURES















- •Video channels: 4, audio channels: 1
- •Recording speed up to 100 fps
- •Internal HDDs mount: up to 1
- •Monitor outputs (main): 3
- •Advanced network software


COMPLIANCE







DIMENSIONS



VIDEO

Video Input	4 x BNC
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI, 1 x VGA, 1 x BNC
AUDIO	
Audio Input/Output	1 x RCA/1 x RCA

RECORDING

Compression	H.264
Recording Speed	100 fps (960 x 576) • 100 fps (720 x 576) • 100 fps (720 x 288) • 100 fps (360 x 288)
Recording Mode	time-lapse, triggered by: REC/PANIC button, motion detection
Schedule	individual settings for: each camera, each day of the week, configuration with an accuracy of: 60 min, possibility of combining individual recording modes

up to 5 s/up to 2 min

ΡΙ ΔΥΒΔΟΚ

Prealarm/Postalarm

FLATBACK	
Playback Speed	100 fps (25 fps per channel)
Recorded Data Search	by date/time, events

BACKUP

Backup Methods	USB port (HDD or Flash memory), network
Backup File Format	AVI, DAT
STORAGE	

available mount: 1 x HDD 3.5" SATA (without DVD-RW) *

Total Capacity

Internal storage

ALARM	
Motion Detection	22 x 15 grid, individual settings of sensitivity
System Reaction to Alarm Events	buzzer, e-mail, screen message, recording activation

4 TB

NETWORK

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
PC/MAC Software	B-Viewer, CMS, NMS, Internet Explorer/-
Mobile applications	Super Live Pro (iPhone), Super Cam (Android, BlackBerry), Pocket Camera (Windows Mobile, Symbian)
Max. Number of Connections with DVR	7 (live monitoring: 5, playback: 1, configuration: 1)

AUXILIARY INTERFACES





Digital Video Recorder NDR-BA3104-II

USB Ports 2 x USB 2.0

OPERATING SYSTEM

Operating System	Linux
Operation Mode	quadruplex
OSD	languages: Polish, English, Russian, others
Control	front panel, IR remote controller, PC mouse (in-set included), network
System Diagnostic	automatic control of: HDDs

INSTALLATION PARAMETERS

Dimensions (mm)	255 (W) x 50 (H) x 210 (D)
Weight	2 kg (without HDDs)
Power Supply	12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)
Power Consumption	25 W (with 1 HDD)
Operating Temperature	0°C ~ 50°C

^{*} List of compatible HDD models and maximum of their capacities is available in section DOWNLOADABLE FILES.

