

Bullet IP Camera with Motor-zoom Lens

NVIP-4DN3552AH/IR-1P

6000 VSS
IP



KEY FEATURES



- Resolution: 4 MPX
- Lens: motorized, auto-focus function, f=9 ~ 22 mm/F1.4
- D/N function - IR cut filter
- Video content analysis
- SD card support
- WDR with double scan sensor
- Min. Illumination from 0.07 lx
- IR LED, range up to 100 m

DIMENSIONS



IMAGE

Image Sensor	4 MPX CMOS sensor 1/3" OmniVision
Number of Effective Pixels	2688 (H) x 1520 (V)
Min. Illumination	0.07 lx/F1.4 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 25 s ~ 1/100000 s
Digital Slow Shutter (DSS)	up to 1/3 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes

LENS

Lens Type	motorized, f=9 ~ 22 mm/F1.4
Auto-focus	zoom trigger, day/night mode trigger, manual trigger

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Delay	2 ~ 120 s
Switching Schedule	yes
Visible Light Sensor	yes

NETWORK

Stream Resolution	2560 x 1440 (QHD), 2592 x 1520, 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA)
Frame Rate	30 fps for and lower resolutions
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.265, MJPEG/G.711
Number of Simultaneous Connections	max. 5
Bandwidth	30 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, IPv6, UDP, HTTPS, Multicast, FTP, DHCP, DDNS, NTP, SNTP, RTSP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP
ONVIF Protocol Support	Profile G/S
Camera Configuration	from Internet Explorer, Chrome browser • languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NVR-6000 Viewer

Bullet IP Camera with Motor-zoom Lens NVIP-4DN3552AH/IR-1P

Mobile applications

SuperLive Plus (iPhone, Android)

VIDEO ANALYTICS

Functions	tamper, abandoned object, object disappearance, line cross, zone entrance, multi loiter, scene change, video blurred, video color cast
-----------	--

OTHER FUNCTIONS

Privacy Zones	4 video mask type: single color or 1 video mask type: mosaic
Motion Detection	yes
Region of interest (ROI)	3
Image Processing	180° image rotation, sharpening, mirror effect, corridor mode
Prealarm/Postalarm	-/up to 120 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation

IR LED

LED Number	4
Range	100 m
Angle	90°

INTERFACES

Video Output	BNC, 1.0 Vp-p, 75 Ohm
Alarm Input/Output	1 (NO/NC)/1
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	SD - capacity up to 128GB

INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 109 (Φ) x 360 (L)
Weight	1.7 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Surge protection	TVS 4000 V
Power Consumption	8 W • 16 W (IR illuminator on)
Operating Temperature	-20°C ~ 50°C

Some functions are available from 4.2.1 software version