

Vandal Proof AHD Camera

NVAHD-4DN3202V/IR-1-II



KEY FEATURES



KEY FEATURES

- D/N function - IR cut filter
- resolution 4MPX
- Lens: varifocal, $f=2.7 \sim 13.5$ mm/F1.3
- Min. Illumination: 0.03 lx (0 lx, IR on)
- IR LED, range up to 30 m

DIMENSIONS



IMAGE

Image Sensor	CMOS sensor 1/3" OV
Operating mode	AHD 4MPX
Number of Effective Pixels	2688 (H) x 1520 (V)
Resolution	4MPX
Min. Illumination	0.03 lx/F1.3 - color mode • 0 lx (IR on) - B/W mode
S/N Ratio	> 50 dB (AGC off)
Electronic Shutter	auto: 1/25 s ~ 1/50000 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D

LENS

Lens Type	varifocal, $f=2.7 \sim 13.5$ mm/F1.3
-----------	--------------------------------------

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual
Switching Delay	0 ~ 60 s
Visible Light Sensor	yes

OTHER FUNCTIONS

OSD	languages: Polish, English, Russian, others
Image Processing	Defective Pixel Correction (DPC), lens vignetting correction, 180° image rotation, sharpening, mirror effect
Remote control	Yes (COAX protocol)

IR LED

LED Number	30
Range	30 m
Angle	120°

INTERFACES

Video Output	BNC, 1.0 Vp-p, 75 Ohm
--------------	-----------------------

INSTALLATION PARAMETERS

Dimensions (mm)	135 (Ø) x 128 (H)
Weight	0.7 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	vandalproof, aluminium, white



Vandal Proof AHD Camera **NVAHD-4DN3202V/IR-1-II**

Power Supply	12 VDC
Power Consumption	1 W • 5 W (IR illuminator on)
Operating Temperature	-30°C ~ 55°C

Access to the OSD and enable/configuration camera options require the use of AHD DVR with COAX function

