

Bullet IP LPR Camera with Motor-zoom Lens NVIP-2DN5021H/IRH-1P/LPR

5000
IP SERIES



KEY FEATURES



- Resolution: 2 MPX
- Lens: motorized, auto-iris and auto-focus function, $f=7 \sim 22$ mm/F1.2
- D/N function - IR cut filter
- Licence plate recognition (LPR)
- SD card support
- Min. Illumination from 0.01 lx (0 lx, IR on)
- IR LED, range up to 70 m

DIMENSIONS



IMAGE

Image Sensor	2 MPX CMOS sensor 1/2.9" SONY Exmor
Number of Effective Pixels	1984 (H) x 1105 (V)
Min. Illumination	0.01 lx/F1.2 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1 s ~ 1/10000 s
Digital Slow Shutter (DSS)	up to 1 s
Wide Dynamic Range (WDR)	yes
Digital Image Stabilization (DIS)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes

LENS

Lens Type	motorized, auto-iris function, $f=7 \sim 22$ mm/F1.2
Auto-focus	zoom trigger, manual trigger

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Delay	0 ~ 180 s
Switching Schedule	yes
Visible Light Sensor	yes

NETWORK

Stream Resolution	1920 x 1080 (Full HD), 1280 x 720 (HD), 704 x 576, 704 x 480, 640 x 480 (VGA), 640 x 360, 352 x 288 (CIF), 320 x 240 (QVGA)
Frame Rate	30 fps for and lower resolutions
Multistreaming Mode	number of streams: 2
Video/Audio Compression	H.264, MJPEG/G.711, RAW_PCM
Number of Simultaneous Connections	max. 8
Bandwidth	25 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, UDP, HTTPS, Multicast, FTP, DHCP, DNS, DDNS, NTP, RTSP, PPPoE, SMTP
ONVIF Protocol Support	Profile S
Camera Configuration	from Internet Explorer browser • languages: Polish, English, Russian, and others

Bullet IP LPR Camera with Motor-zoom Lens NVIP-2DN5021H/IRH-1P/LPR

Compatible Software

NOVUS MANAGEMENT SYSTEM VSS

OTHER FUNCTIONS

Privacy Zones	4
Motion Detection	yes
Region of interest (ROI)	5
Image Processing	180° image rotation, sharpening, mirror effect, corridor mode
Prealarm/Postalarm	up to 5 MB/up to 86400 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card

LICENCE PLATE RECOGNITION (LPR)

Autonomous operation mode	yes - recognition function implemented in the camera
Types of recognized number plates	all countries of the European Union / CIS countries / Turkey / Israel / Switzerland / Norway and others
Barrier control	yes - built-in relay output
Recommended maximum speed of the vehicle	up to 50 km/h
Data recorded in the camera base	recognition date/time, number of recognised licence plate, image of recognised licence plate, vehicle movement direction, system reaction, presence on the "white list" or "black list", country of origin of the registration plate
Reactions for the licence plate recognition	e-mail with attachment, saving file on FTP server, alarm output activation

IR LED

LED Number	17
Range	70 m
Angle	50°

INTERFACES

Video Output	BNC, 1.0 Vp-p, 75 Ohm - maintenance only
Audio Input/Output	1 x RCA/1 x RCA
Alarm Input/Output	1 (NO/NC)/1 relay type (max. 12VDC/300mA)
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	SD - capacity up to 64GB

INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 110 (Φ) x 377 (L)
Weight	1.7 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Power Consumption	6 W • 15 W (IR and heater on)
Operating Temperature	-30°C ~ 60°C
Humidity	max. 90%, relative (non-condensing)
Built-in Heater/Fan	yes/no