Bullet IP Camera

NVIP-5DN3612H/IR-1P/F



KEY FEATURES

- •Resolution: 5 MPX
- •Lens: varifocal, f=2.8 ~ 12 mm/F1.4
- •D/N function - IR cut filter
- •Video content analysis
- •WDR with double scan sensor
- •Min. Illumination: 0.01 lx (0 lx, IR on)
- •IR LED, range up to 30 m

DIMENSIONS



87 mm (Ø)



219 mm

IMAGE

Image Sensor	5 MPX CMOS sensor 1/2.5” APTINA
Number of Effective Pixels	2592 (H) x 1944 (V)
Min. Illumination	0.01 lx/F1.4 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/3 s ~ 1/100000 s
Digital Slow Shutter (DSS)	up to 1/3 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes

LENS

Lens Type	varifocal, f=2.8 ~ 12 mm/F1.4

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Delay	2 ~ 120 s
Switching Schedule	yes
Visible Light Sensor	yes

NETWORK

Stream Resolution	2560 x 1440 (QHD), 2592 x 1520, 2592 x 1944, 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA)
Frame Rate	30 fps for • 60 fps for and lower resolutions
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.265, MJPEG/G.711
Number of Simultaneous Connections	max. 6
Bandwidth	60 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, IPv4/v6, UDP, HTTPS, Multicast, FTP, DHCP, DDNS, RTSP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP
ONVIF Protocol Support	Profile G/S
Camera Configuration	from Internet Explorer, Chrome browser • languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS

VIDEO ANALYTICS

Bullet IP Camera
NVIP-5DN3612H/IR-1P/F

Functions	tamper, abandoned object, object disappearance, line cross, zone entrance, object counting, multi loiter, face detection

OTHER FUNCTIONS

Privacy Zones	4
Motion Detection	yes
Region of interest (ROI)	3
Image Processing	180˚ image rotation, sharpening, mirror effect, corridor mode
Prealarm/Postalarm	-/up to 120 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server

IR LED

LED Number	36
Range	30 m
Angle	120°

INTERFACES

Video Output	BNC, 1.0 Vp-p, 75 Ohm
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s

INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 87 (Φ) x 219 (L)
Weight	0.6 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included , IK10 impact rating
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Power Consumption	3 W • 8 W (IR illuminator on)
Operating Temperature	-30°C ~ 60°C