

8-channel IP Recorder

NVR-6208P8-H1



6000 

KEY FEATURES



- 8 x PoE Ethernet ports
- 8 x video and audio channels
- Recording speed up to 240 fps at 2592 x 1944
- Supports resolution up to 2592 x 1944
- Recorded stream size: 40 Mb/s in total from all cameras
- 1 x internal place for HDD mounting
- 2 x monitor outputs (HDMI, VGA)
- Intelligent image analysis

DIMENSIONS



The recorder is dedicated to work with NOVUS 6000 series IP cameras. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

VIDEO

IP Cameras	up to 8 channels at 2592 x 1944 resolution (video + audio)
Maximum Supported Camera Resolution	2592 x 1944
Compression	H.264, H.265, H.265+, H.265 Smart
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI, 1 x VGA (up to 2 monitors simultaneously)
Dualstreaming Support	yes
Fisheye Support	yes, 6000 IP series cameras • using ipGO 6, Internet Explorer, N Control 6000

AUDIO

Audio Input/Output	- / 1 x HDMI
--------------------	--------------

RECORDING

Stream Size	40 Mb/s in total from all cameras
Recording Mode	continuous, triggered by: manual, alarm input, motion detection, intelligent image analysis functions
Prealarm/Postalarm	up to 5 s/up to 600 s

DISPLAY

Display Speed	240 fps (8 x 30 fps)
---------------	----------------------

PLAYBACK

Playback Speed	240 fps (8 x 30 fps for 2592 x 1944) • 240 fps (8 x 30 fps)
Recorded Data Search	by date/time, events, image analysis events, POS, motion in a defined area, tags

BACKUP

Backup Methods	USB port (HDD or Flash memory), network
Backup File Format	MP4, AVI, RPAS (player included)

STORAGE

Internal Storage	available mount: 1 x HDD 3.5" 6 TB SATA
Total Internal Capacity	6 TB

ALARM

Camera Alarm Input/Output	supports IP camera's alarm input/output
Motion Detection	supports camera's motion detection

**8-channel IP Recorder
NVR-6208P8-H1**

System Reaction to Alarm Events buzzer, alarm output activation, recording activation, PTZ, e-mail with attachment, Full Screen, PUSH message, voice prompt, snapshot

INTELLIGENT IMAGE ANALYSIS

Supported Functions	Exception, Scene Change, Video Blurred, Video Color Cast, Tripwire, Zone entrance, Abandoned Object, Object Disappearance, Face Detection, Perimeter Intrusion Detection by pedestrian or vehicle, Line Cross Detection by pedestrian or vehicle, License Plate Recognition (LPR)
---------------------	---

Database Capacity	1000 license plates
-------------------	---------------------

NETWORK

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s • 8 x Ethernet PoE (IEEE802.3af, Class 3) - RJ-45 interface, 10/100 Mbit/s
-------------------	--

Network Protocols Support	HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SNMP, IEEE 802.1X, PPPoE, SMTP, P2P, POS, HTML5
---------------------------	--

ONVIF Protocol Support	S profile (ONVIF 2.2 or higher)
------------------------	---------------------------------

PC/MAC Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000
-----------------	--

Mobile applications	ipGO 6 (iPhone, Android)
---------------------	--------------------------

Number of Simultaneous Connections	up to 5 clients, up to 12 main streams or 32 substreams or 8 playback streams in total
------------------------------------	--

Bandwidth	40 Mb/s in total to all client workstations
-----------	---

PTZ

PTZ Functions	pan/tilt/zoom, preset commands
---------------	--------------------------------

AUXILIARY INTERFACES

USB Ports	2 x USB 2.0
-----------	-------------

OPERATING SYSTEM

Operating System	Linux
------------------	-------

OSD	languages: Polish, English, others
-----	------------------------------------

Control	PC mouse (in-set included), network
---------	-------------------------------------

System Diagnostic	automatic control of: HDDs, network, camera connection loss
-------------------	---

Security	password protection, IP filtering, MAC filtering, ARP guard
----------	---

INSTALLATION PARAMETERS

Dimensions (mm)	255 (W) x 42 (H) x 233 (D)
-----------------	----------------------------

Weight	0.84 kg (without HDD)
--------	-----------------------

Power Supply	48 VDC (100 ~ 240 VAC/48 VDC PSU in-set included)
--------------	---

Power Consumption	15 W (with 1 HDD) + 105 W PoE
-------------------	-------------------------------

Operating Temperature	-10°C ~ 50°C
-----------------------	--------------

The availability of individual functions (including image analysis) depends on the model of the cameras used, as well as the software version of the recorder and cameras.

Presented display and playback speeds are achieved using dual-streaming. Detailed data on hard drives can be found in the compatibility table available in the DOWNLOADABLE FILES tab.