# **NoVus**

# 8-channel IP Recorder

## NVR-6208P8-H1





#### **KEY FEATURES**























- •8 x PoE Ethernet ports
- •8 x video and audio channels
- $\bullet$ Recording speed up to 240 fps at 2592 x 1944
- •Supports resolution up to 2592 x 1944
- Recorded stream size: 40 Mb/s in total from all cameras
- ullet 1 x internal place for HDD mounting
- •2 x monitor outputs (HDMI, VGA)
- •Intelligent image analysis

### **DIMENSIONS**







The recorder is dedicated to work with NOVUS 6000 series IP cameras. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

#### **VIDEO**

IP Cameras	up to 8 channels at 2592 x 1944 resolution (video + audio)
Maximum Supported Camera Resolution	2592 x 1944
Compression	H.264, H.265, H.265+, H.265 Smart
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI, 1 x VGA (up to 2 monitors simultaneously)
Dualstreaming Support	yes
Fisheye Support	yes, 6000 IP series cameras • using ipGO 6, Internet Explorer, N Control 6000
AUDIO	
Audio Input/Output	- / 1 x HDMI
RECORDING	
Stream Size	40 Mb/s in total from all cameras
Recording Mode	continuous, triggered by: manual, alarm input, motion detection, intelligent image analysis functions
Prealarm/Postalarm	up to 5 s/up to 600 s
DISPLAY	
Display Speed	240 fps (8 x 30 fps)
PLAYBACK	
Playback Speed	240 fps (8 x 30 fps for 2592 x 1944) • 240 fps (8 x 30 fps)
Recorded Data Search	by date/time, events, image analysis events, POS, motion in a defined area, tags
BACKUP	
Backup Methods	USB port (HDD or Flash memory), network
Backup File Format	MP4, AVI, RPAS (player included)
STORAGE	
Internal Storage	available mount: 1 x HDD 3.5" 6 TB SATA
Total Internal Capacity	6 TB
ALARM	
Camera Alarm Input/Output	supports IP camera's alarm input/output

supports camera's motion detection



Motion Detection



# 8-channel IP Recorder NVR-6208P8-H1

System Reaction to Alarm Events	buzzer, alarm output activation, recording activation, PTZ, e-mail with
	atatchment Full Screen PUSH message voice prompt spanshot

System Nedection to Alaim Events	atatchment, Full Screen, PUSH message, voice prompt, snapshot
INTELLIGENT IMAGE ANALYS	GIS
Supported Functions	Exception, Scene Change, Video Blurred, Video Color Cast, Tripwire, Zone entrance, Abandoned Object, Object Disappearance, Face Detection, Perimeter Intrusion Detection by pedestrian or vehicle, Line Cross Detection by pedestrian or vehicle, License Plate Recognition (LPR)
Database Capacity	1000 license plates
NETWORK	
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s • 8 x Ethernet PoE (IEEE802.3af, Class 3) - RJ-45 interface, 10/100 Mbit/s
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SNMP, IEEE $802.1X$ , PPPoE, SMTP, P2P, POS, HTML5
PC/MAC Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000
Mobile applications	ipGO 6 (iPhone, Android)
Number of Simultaneous Connecti	onsup to 5 clients, up to 12 main streams or 32 substreams or 8 playback streams in total
Bandwidth	40 Mb/s in total to all client workstations
PTZ	
PTZ Functions	pan/tilt/zoom, preset commands
AUXILIARY INTERFACES	
USB Ports	2 x USB 2.0
OPERATING SYSTEM	
Operating System	Linux
OSD	languages: Polish, English, others
Control	PC mouse (in-set included), network
System Diagnostic	automatic control of: HDDs, network, camera connection loss
Security	password protection, IP filtering, MAC filtering, ARP guard
INSTALLATION PARAMETERS	5
Dimensions (mm)	255 (W) x 42 (H) x 233 (D)
Weight	0.84 kg (without HDD)
Power Supply	48 VDC (100 ~ 240 VAC/48 VDC PSU in-set included)
Power Consumption	15 W (with 1 HDD) + 105 W PoE
Operating Temperature	-10°C ~ 50°C

The availability of individual functions (including image analysis) depends on the model of the cameras used, as well as the software version of the recorder and cameras. Presented display and playback speeds are achieved using dual-streaming. Detailed data on hard drives can be found in the compatibility table available in the DOWNLOADABLE FILES tab.



