


IP Recorder

NVR-6332-H8/F



KEY FEATURES



•32 x video and audio channels •Recording speed up to 960 fps at 3840 x 2160 •Supports resolution up to 3840 x 2160

•Recorded stream size: 256 Mb/s in total from all cameras •8 x internal place for HDD mounting

•3 x monitor outputs (HDMI 4K UltraHD, HDMI, VGA) Face recognition

DIMENSIONS



Resolution			
Compression	H.264, H.264+, H.265		
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI (4K UltraHD), 1 VGA • spot: 1 x HDMI (FullHD)		
Dualstreaming Support	yes*		
AUDIO			
Audio Input/Output	- / 1 x line-out (RCA)		
RECORDING			
Stream Size	256 Mb/s in total from all cameras		
Recording Mode	continuous, triggered by: manual, alarm input, motion detection		
Prealarm/Postalarm	up to 5 s/up to 600 s		
DISPLAY			
Display Speed	960 fps (32 x 30 fps)*		
PLAYBACK			
Playback Speed	480 fps (16 x 30 fps for 3840 x 2160) *		
Recorded Data Search	by date/time, events, related to face recognition		
BACKUP			
Backup Methods	USB port (HDD or Flash memory), network		
Backup File Format	AVI		
STORAGE			
Internal Storage	available mount: 8 x HDD 3.5" 14 TB SATA		
Total Internal Capacity	112 TB		
ALARM			
Internal Alarm Input/Output	8/4 relay type (max. 12VDC/1A)		
Camera Alarm Input/Output	supports IP camera's alarm input/output		
Motion Detection	supports camera's motion detection		
System Reaction to Alarm Events	buzzer, e-mail, alarm output activation, recording activation, PTZ		
INTELLIGENT IMAGE ANALYS	IS		
Supported Functions	Exception, Scene Change, Video Blurred, Video Color Cast, Tripwire, Zone entrance, Abandoned Object, Object Disappearance, Face Recognition		

5000 faces • 1000 license plates

NoVus

Database Capacity





IP Recorder NVR-6332-H8/F

Ν	БŢ	·w	n	PK
		vv	U	N N

NEIWORK			
Network Interface	2 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s		
Network Protocols Support	HTTP, TCP/IP, IPv4, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP SNMP, SMTP		
PC/MAC Software	Internet Explorer, NVR-6000 Viewer/NVR-6000 Viewer		
Mobile applications	SuperLive Plus (iPhone, Android)		
Number of Simultaneous Connect	ionsup to 4 clients		
Bandwidth	256 Mb/s in total to all client workstations		
PTZ			
PTZ Functions	pan/tilt/zoom, preset commands		
AUXILIARY INTERFACES			
USB Ports	2 x USB 2.0, 1 x USB 3.0		
OPERATING SYSTEM			
Operating System	Linux		
Operation Mode	triplex		
OSD	languages: Polish, English, others		
Control	PC mouse and IR remote controller (in-set included), network		
System Diagnostic	automatic control of: HDDs, network, camera connection loss		
Security	password protection, IP filtering, MAC filtering		
INSTALLATION PARAMETER	s		
Dimensions (mm)	445 (W) x 90 (H) x 436 (D)		
Weight	6 kg (without HDD)		
Power Supply	100 ~ 240 VAC		
Power Consumption	175 W (with 8 HDDs)		
Operating Temperature	-10°C ~ 50°C		

Support for intelligent image analysis works only with NOVUS IP 3000 series cameras The availability of the following functions: double-stream operation, motion detection, alarm inputs / outputs, PTZ control depends on the functionality of the given camera and the capabilities of the communication protocol. Detailed data can be found in the compatibility table available in the DOWNLOADS tab.

* Available with dual streaming mode.

