NOVUS

Multistandard AHD Recorder

NHDR-4108AHD





hybrid mode: 16 Mb/s in total from all IP cameras • IP mode: 48 Mb/s

continuous, triggered by: REC/PANIC button, alarm input, motion

KEY FEATURES





















- •Video channels: 8, audio channels: 8
- •Recording speed: up to 240 fps (AHD), up to 360 fps
- •Internal HDDs mount: up to 2
- •Monitor outputs (main): 2
- ·Supports HD analog cameras (720p, 1080p, 4MPX,
- •Supports AHD, TVI, CVI cameras
- •IP cameras support (hybrid mode)
- •Intelligent image analysis
- •PIR cameras support
- •Supports POS devices

DIMENSIONS





| VIDEO | |
|-------------------------|--|
| Video Input | 8 x BNC |
| Operating mode | AHD 5Mpx, TVI 5Mpx, CVI 4Mpx, analog 960H |
| Monitor Output | main (split screen, full screen, sequence): 1 x HDMI (FullHD), 1 x VGA (FullHD) |
| IP Streams | DVR mode: $8 \times BNC + 0 \times IP \cdot hybrid mode: 8 \times BNC + 4 \times IP \cdot IP mode: 0 \times BNC + 12 \times IP$ |
| Supported IP resolution | max. 2592 x 1944 |
| AUDIO | |
| Audio Input/Output | 8 x RCA (Line-in)/1 x HDMI, 1 x RCA |
| RECORDING | |
| Compression | H.264, H.265 |
| Recording Speed | 240 fps (1280 x 720 - HD) • 120 fps (1920 x 1080 - FullHD) • 144 fps (1280 x 1440 - 4Mpx Lite) • 120 fps (1280 x 1944 - 5Mpx Lite) • 56 fps (2560 x 1440 - 4Mpx) |
| IP recording speed | hybrid mode: 120fps • IP mode: 360fps |

Schedule individual settings for: each camera, each day of the week, configuration with an accuracy of: 30 min, possibility of combining individual recording modes

| ΡI | _A | Υ | R | Δ | C | K |
|----|-----|---|---|---|---|----|
| | -/~ | | _ | _ | • | 87 |

Prealarm/postalarm

IP stream size

Recording Mode

| Playback speed | 240 fps |
|----------------------|---|
| IP playback speed | 240 fps |
| Recorded Data Search | by date/time, events, image analysis events, motion in a defined area, tags |

in total from all IP cameras

detection, PIR alarm

up to 3 s/up to 5 min

BACKUP

| Backup Methods | USB port (HDD or Flash memory), network | |
|-------------------------|---|--|
| Backup File Format | JPG, BMP, PNG, MP4, AVI | |
| STORAGE | | |
| Internal storage | available mount: 2 x HDD 3.5" SATA | |
| Total Internal Capacity | 28 TB | |

ALARM

| Alarm Input/Output | 8/1 relay type |
|----------------------|-----------------|
| / warm inpacy output | of I relay type |





Multistandard AHD Recorder NHDR-4108AHD

| Motion Detection | 36 x 44 grid, individual settings of sensitivity, PIR cameras support |
|--|--|
| System Reaction to Alarm Events | buzzer, e-mail, alarm output activation, screen message, recording activation, PTZ, Full Screen, FTP picture upload, FTP video upload, picture to Cloud, video to Cloud |
| INTELLIGENT IMAGE ANALYSIS | S |
| Supported functions | Exception, Line cross, Zone entrance, Abandoned object, Object disappearance, Face detection, Pedestrian detestion, Cross counting, Sound detection |
| Number of channels | 0 x BNC, 12 x IP (2000 and 4000 Serie) |
| NETWORK | |
| Network Interface | 1 x Ethernet - RJ-45 interface, 10/100 Mbit/s |
| Network Protocols Support | HTTP, TCP/IP, IPv4, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SNMP, SMTP, P2P |
| PC/MAC Software | NMS, Internet Explorer, NHDR-5000 Viewer/NHDR-5000 Viewer |
| Mobile applications | RxCamView (iPhone, Android) |
| Number of Simultaneous Connection | sup to 20 (live monitoring: 20, playback: 1, configuration: 20) |
| Bandwidth | 64 Mb/s in total to all client workstations |
| PTZ | |
| PTZ Ports | 1 x RS-485 |
| PTZ Protocols | Pelco-D, Pelco-P |
| PTZ Functions | pan/tilt/zoom, preset commands, patterns |
| COAX | |
| | |
| COAX Functions | menu, zoom, focus, PTZ |
| COAX Functions POS | menu, zoom, focus, PTZ |
| | menu, zoom, focus, PTZ 4 |
| POS | |
| POS Number of POS channels | 4 |
| POS Number of POS channels POS Interface | 4 Ethernet, RS485 |
| POS Number of POS channels POS Interface POS Functions | 4 Ethernet, RS485 |
| POS Number of POS channels POS Interface POS Functions AUXILIARY INTERFACES USB Ports | 4 Ethernet, RS485 display text on the video, keyword search, export text with the video |
| POS Number of POS channels POS Interface POS Functions AUXILIARY INTERFACES | 4 Ethernet, RS485 display text on the video, keyword search, export text with the video |
| POS Number of POS channels POS Interface POS Functions AUXILIARY INTERFACES USB Ports OPERATING SYSTEM | 4 Ethernet, RS485 display text on the video, keyword search, export text with the video 2 x USB 2.0, |
| POS Number of POS channels POS Interface POS Functions AUXILIARY INTERFACES USB Ports OPERATING SYSTEM Operating System | 4 Ethernet, RS485 display text on the video, keyword search, export text with the video 2 x USB 2.0, Linux |
| POS Number of POS channels POS Interface POS Functions AUXILIARY INTERFACES USB Ports OPERATING SYSTEM Operating System OSD | 4 Ethernet, RS485 display text on the video, keyword search, export text with the video 2 x USB 2.0, Linux languages: Polish, English, Russian, others PC mouse and IR remote controller (in-set included), network, NV- |
| POS Number of POS channels POS Interface POS Functions AUXILIARY INTERFACES USB Ports OPERATING SYSTEM Operating System OSD Control | 4 Ethernet, RS485 display text on the video, keyword search, export text with the video 2 x USB 2.0, Linux languages: Polish, English, Russian, others PC mouse and IR remote controller (in-set included), network, NV-KBD50 keyboard |
| POS Number of POS channels POS Interface POS Functions AUXILIARY INTERFACES USB Ports OPERATING SYSTEM Operating System OSD Control System Diagnostic | 4 Ethernet, RS485 display text on the video, keyword search, export text with the video 2 x USB 2.0, Linux languages: Polish, English, Russian, others PC mouse and IR remote controller (in-set included), network, NV-KBD50 keyboard automatic control of: HDDs, camera connection loss |
| POS Number of POS channels POS Interface POS Functions AUXILIARY INTERFACES USB Ports OPERATING SYSTEM Operating System OSD Control System Diagnostic Security | 4 Ethernet, RS485 display text on the video, keyword search, export text with the video 2 x USB 2.0, Linux languages: Polish, English, Russian, others PC mouse and IR remote controller (in-set included), network, NV-KBD50 keyboard automatic control of: HDDs, camera connection loss |
| POS Number of POS channels POS Interface POS Functions AUXILIARY INTERFACES USB Ports OPERATING SYSTEM Operating System OSD Control System Diagnostic Security INSTALLATION PARAMETERS | 4 Ethernet, RS485 display text on the video, keyword search, export text with the video 2 x USB 2.0, Linux languages: Polish, English, Russian, others PC mouse and IR remote controller (in-set included), network, NV-KBD50 keyboard automatic control of: HDDs, camera connection loss password protection, IP filtering |
| POS Number of POS channels POS Interface POS Functions AUXILIARY INTERFACES USB Ports OPERATING SYSTEM Operating System OSD Control System Diagnostic Security INSTALLATION PARAMETERS Dimensions (mm) | 4 Ethernet, RS485 display text on the video, keyword search, export text with the video 2 x USB 2.0, Linux languages: Polish, English, Russian, others PC mouse and IR remote controller (in-set included), network, NV-KBD50 keyboard automatic control of: HDDs, camera connection loss password protection, IP filtering 378 (W) x 50 (H) x 340 (D) |
| POS Number of POS channels POS Interface POS Functions AUXILIARY INTERFACES USB Ports OPERATING SYSTEM Operating System OSD Control System Diagnostic Security INSTALLATION PARAMETERS Dimensions (mm) Weight | 4 Ethernet, RS485 display text on the video, keyword search, export text with the video 2 x USB 2.0, Linux languages: Polish, English, Russian, others PC mouse and IR remote controller (in-set included), network, NV-KBD50 keyboard automatic control of: HDDs, camera connection loss password protection, IP filtering 378 (W) x 50 (H) x 340 (D) 2.5 kg (without HDDs) |
| POS Number of POS channels POS Interface POS Functions AUXILIARY INTERFACES USB Ports OPERATING SYSTEM Operating System OSD Control System Diagnostic Security INSTALLATION PARAMETERS Dimensions (mm) Weight Power Supply | 4 Ethernet, RS485 display text on the video, keyword search, export text with the video 2 x USB 2.0, Linux languages: Polish, English, Russian, others PC mouse and IR remote controller (in-set included), network, NV-KBD50 keyboard automatic control of: HDDs, camera connection loss password protection, IP filtering 378 (W) x 50 (H) x 340 (D) 2.5 kg (without HDDs) 12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included) |







Multistandard AHD Recorder NHDR-4108AHD

The recorder is dedicated to work with AHD cameras, Novus 2000 and 4000 series IP cameras and achieves the best functionality with them. In case of work with IP cameras intelligent image analysis, dualstream mode, PTZ control, motion detection and alarm inputs / outputs functions depend on the functionality of the IP camera and the capabilities of the communication protocol. Detailed data on camera compatibility with recorders and compatible hard drives can be found in the compatibility tables available in the DOWNLOADABLE FILES tab.

Display and playback speeds are achieved using dual stream.

The recording speed of analog cameras may be limited during playback.



