NOVUS

PoE Extender **NV-101EP**



KEY FEATURES

•1 x 1000Mbps PoE

DIMENSIONS





_		
	E	
	42	
mm		

GENERAL

Device Type	PoE Extender		
NETWORK			
PoE standards	IEEE802.3af, Class 3, IEEE802.3at, Class 4		
PoE modes	Endspan (1,2+ / 3,6-)		
Protocols Support	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T		
Transmission range	The maximum transmission range using 1 x NVS-101EP is 200m, maximum power output: 25W • The maximum transmission range using 2 x NVS-101EP is 300m, maximum power output: 20W		
Connector type	Hermetic RJ45 connector		

INSTALLATION PARAMETERS

Case	Metal, color black	
Dimensions (mm)	45 (W) x 45 (H) x 205 (L)	
Weight	0.25 kg	
Input Voltage	48 - 56VDC	
Power Consumption	30 W (maximum)	
PoE Budget	25 W	
Operating Temperature	-25°C ~ 55°C	

Maximum ranges depend on cable quality, interference and camera model. The ranges were determined in laboratory conditions. For information on the exact ranges for a given camera connection and switches please contact support or perform tests in the real environment of the future operation of the devices.