

Bullet IP Camera with Motor-zoom Lens

NVIP-5H-6402M/F
(NVIP-5DN3613AH/IR-1P/F)

6000 VSS
IP



KEY FEATURES



- Resolution: 5 MPX
- Lens: motorized, auto-focus function, f=2.8 ~ 12 mm/F1.4
- D/N function - IR cut filter
- Video content analysis
- WDR with double scan sensor
- Min. Illumination: 0.017 lx (0 lx, IR on)
- IR LED, range up to 50 m

DIMENSIONS



IMAGE

Image Sensor	5 MPX CMOS sensor 1/2.5" APTINA
Number of Effective Pixels	2592 (H) x 1944 (V)
Min. Illumination	0.017 lx/F1.4 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/3 s ~ 1/100000 s
Digital Slow Shutter (DSS)	up to 1/3 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes

LENS

Lens Type	motorized, f=2.8 ~ 12 mm/F1.4
Auto-focus	zoom trigger, day/night mode trigger, manual trigger

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Delay	2 ~ 120 s
Switching Schedule	yes
Visible Light Sensor	yes

NETWORK

Stream Resolution	2560 x 1440 (QHD), 2592 x 1520, 2592 x 1944, 1920 x 1080 (Full HD), 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA)
Frame Rate	30 fps for and lower resolutions
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.264+, H.265, H.265+, MJPEG/G.711
Number of Simultaneous Connections	max. 6
Bandwidth	60 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, IPv4/v6, UDP, HTTPS, Multicast, FTP, DHCP, DDNS, NTP, RTSP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, SSL, ICMP, Unicast
ONVIF Protocol Support	Profile G/S
Camera Configuration	from Internet Explorer browser • languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NVR-6000 Viewer

Bullet IP Camera with Motor-zoom Lens NVIP-5H-6402M/F (NVIP-5DN3613AH/IR-1P/F)

Mobile applications SuperLive Plus (iPhone, Android)

VIDEO ANALYTICS

Functions tamper, abandoned object, object disappearance, line cross, zone entrance, object counting, multi loiter, face detection

OTHER FUNCTIONS

Privacy Zones 4 video mask type: single color or 1 video mask type: mosaic

Motion Detection yes

Region of interest (ROI) 3

Image Processing 180° image rotation, sharpening, mirror effect, corridor mode

Prealarm/Postalarm -/up to 120 s

System Reaction to Alarm Events e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation

Restoring default settings via web browser, using reset button, via NMS IPTool software

IR LED

LED Number 48

Range 50 m

Angle 120°

Smart IR yes (software support)

INTERFACES

Video Output BNC, 1.0 Vp-p, 75 Ohm

Audio Input/Output 1 x Jack (3.5 mm)/1 x Jack (3.5 mm)

Alarm Input/Output 1 (NO/NC)/1

RS-485 yes

Network Interface 1 x Ethernet - RJ-45 interface, 10/100 Mbit/s

Memory Card Slot microSD - capacity up to 128GB

INSTALLATION PARAMETERS

Dimensions (mm) with bracket: 109 (Φ) x 284 (L)

Weight 1.1 kg

Degree of Protection IP 66 (details in the user's manual)

Enclosure aluminium, white, fully cable managed wall mount bracket in-set included, IK10 impact rating

Power Supply 12 VDC, PoE (IEEE 802.3af, Class 3)

Surge protection TVS 4000 V

Power Consumption 6 W • 9 W (IR illuminator on)

Operating Temperature -30°C ~ 60°C

Humidity max. 95%, relative (non-condensing)