NoVus

Hardened 8-port PoE+ Switch

NVS-3208SP-EH



KEY FEATURES



KEY FEATURES

- •8 x 100Mbps PoE+
- •2 x 1000Mb/s SFP UPLINK
- •Operating temperature: -40°C \div 70°C

DIMENSIONS



GENERAL

Device Type	Hardened PoE+ switch
NETWORK	
Ports	PoE+ Ports: 8 x 10/100Mbps (the number of ports simultaneously operating with PoE + mode is limited by PoE budget) • Optical UPLINK ports: 2 x SFP
PoE standards	IEEE802.3af, Class 3, IEEE802.3at, Class 4
PoE modes	Endspan (1,2+ / 3,6-)
Switching capacity	5.6 Gb/s
Protocols Support	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3x
MAC address list	4K

INSTALLATION PARAMETERS

Case	Metal, color navy blue, enclosure with possibility to mount on DIN TH35 rail
Dimensions (mm)	162 (W) x 110 (H) x 45 (L)
Weight	0.7 kg
Input Voltage	48 VDC (power supply 100 ~ 240 VAC/48 VDC Included)
Power Consumption	144 W (maximum)
PoE Budget	130 W for ports 1 to 8, up to 30 W for one port
Operating Temperature	-40°C ~ 70°C

