

## Bullet IP Camera

**NVIP-2H-6201 (NVIP-2DN3130H/IR-1P)**

**6000 VSS IP**



### KEY FEATURES



- Resolution: 2 MPX
- Lens: fixed focal, f=2.8 mm/F1.85
- D/N function - IR cut filter
- Video content analysis
- Min. Illumination from 0.016 lx (0 lx, IR on)
- IR LED, range up to 30 m

### DIMENSIONS



### IMAGE

|                               |                                                       |
|-------------------------------|-------------------------------------------------------|
| Image Sensor                  | 2 MPX CMOS sensor 1/2.7" SmartSens                    |
| Number of Effective Pixels    | 1920 (H) x 1080 (V)                                   |
| Min. Illumination             | 0.016 lx/F1.85 - color mode • 0 lx (IR on) - B/W mode |
| Electronic Shutter            | auto: 1/3 s ~ 1/100000 s                              |
| Wide Dynamic Range (WDR)      | yes                                                   |
| Digital Noise Reduction (DNR) | 3D                                                    |
| Defog Function (F-DNR)        | yes                                                   |
| Highlight Compensation (HLC)  | yes                                                   |
| Back Light Compensation (BLC) | yes                                                   |

### LENS

|           |                             |
|-----------|-----------------------------|
| Lens Type | fixed focal, f=2.8 mm/F1.85 |
|-----------|-----------------------------|

### DAY/NIGHT

|                            |                                               |
|----------------------------|-----------------------------------------------|
| Mode                       | day/night switching: mechanical IR cut filter |
| Switching Mode             | auto, manual, time                            |
| Switching Level Adjustment | yes                                           |
| Switching Schedule         | yes                                           |
| Visible Light Sensor       | yes                                           |

### NETWORK

|                                    |                                                                                  |
|------------------------------------|----------------------------------------------------------------------------------|
| Stream Resolution                  | 1920 x 1080 (Full HD), 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA)        |
| Frame Rate                         | 30 fps for and lower resolutions                                                 |
| Multistreaming Mode                | number of streams: 2                                                             |
| Video/Audio Compression            | H.264, H.265, MJPEG/-                                                            |
| Number of Simultaneous Connections | max. 2                                                                           |
| Bandwidth                          | 9 Mb/s in total                                                                  |
| Network Protocols Support          | HTTP, TCP/IP, IPv4, FTP, DHCP, DDNS, NTP, RTSP, UPnP, PPPoE, SMTP                |
| ONVIF Protocol Support             | Profile S                                                                        |
| Camera Configuration               | from Internet Explorer browser • languages: Polish, English, Russian, and others |
| Compatible Software                | NOVUS MANAGEMENT SYSTEM VSS, NVR-6000 Viewer                                     |
| Mobile applications                | SuperLive Plus (iPhone, Android)                                                 |

### VIDEO ANALYTICS

|           |                                                                                  |
|-----------|----------------------------------------------------------------------------------|
| Functions | tamper, line cross, zone entrance, scene change, video blurred, video color cast |
|-----------|----------------------------------------------------------------------------------|

## Bullet IP Camera NVIP-2H-6201 (NVIP-2DN3130H/IR-1P)

### OTHER FUNCTIONS

|                                 |                                                   |
|---------------------------------|---------------------------------------------------|
| Privacy Zones                   | 4                                                 |
| Motion Detection                | yes                                               |
| Region of interest (ROI)        | 3                                                 |
| Image Processing                | 180° image rotation, sharpening, mirror effect    |
| Prealarm/Postalarm              | -/up to 120 s                                     |
| System Reaction to Alarm Events | e-mail with attachment, saving file on FTP server |

### IR LED

|            |      |
|------------|------|
| LED Number | 36   |
| Range      | 30 m |
| Angle      | 90°  |

### INTERFACES

|                   |                                               |
|-------------------|-----------------------------------------------|
| Network Interface | 1 x Ethernet - RJ-45 interface, 10/100 Mbit/s |
|-------------------|-----------------------------------------------|

### INSTALLATION PARAMETERS

|                       |                                                                                               |
|-----------------------|-----------------------------------------------------------------------------------------------|
| Dimensions (mm)       | with bracket: 87 (Φ) x 219 (L)                                                                |
| Weight                | 0.6 kg                                                                                        |
| Degree of Protection  | IP 66 (details in the user's manual)                                                          |
| Enclosure             | aluminium, white, fully cable managed wall mount bracket in-set included , IK10 impact rating |
| Power Supply          | 12 VDC, PoE (IEEE 802.3af, Class 3)                                                           |
| Surge protection      | TVS 4000 V                                                                                    |
| Power Consumption     | 1.2 W • 4.2 W (IR illuminator on)                                                             |
| Operating Temperature | -30°C ~ 60°C                                                                                  |
| Humidity              | max. 95%, relative (non-condensing)                                                           |