

Bullet IP Camera with Motor-zoom Lens NVIP-4H-6202M

6000 VSS IP



KEY FEATURES



- Resolution: 4 MPX
- Lens: motorized, auto-focus function, f=9 ~ 22 mm/F1.4
- D/N function - IR cut filter
- Video content analysis
- SD card support
- WDR with double scan sensor
- Min. Illumination from 0.07 lx
- IR LED, range up to 100 m

DIMENSIONS



IMAGE

Image Sensor	4 MPX CMOS sensor 1/3" OmniVision
Number of Effective Pixels	2688 (H) x 1520 (V)
Min. Illumination	0.07 lx/F1.4 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 25 s ~ 1/100000 s
Digital Slow Shutter (DSS)	up to 1/3 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes

LENS

Lens Type	motorized, f=9 ~ 22 mm/F1.4
Auto-focus	zoom trigger, day/night mode trigger, manual trigger

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Delay	2 ~ 120 s
Switching Schedule	yes
Visible Light Sensor	yes

NETWORK

Stream Resolution	2560 x 1440 (QHD), 2592 x 1520, 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA)
Frame Rate	30 fps for and lower resolutions
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.265, MJPEG/G.711
Number of Simultaneous Connections	max. 5
Bandwidth	30 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, IPv4/v6, UDP, HTTPS, Multicast, FTP, DHCP, DDNS, NTP, SNTP, RTSP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP
ONVIF Protocol Support	Profile G/S
Camera Configuration	from Internet Explorer browser • languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NVR-6000 Viewer

Bullet IP Camera with Motor-zoom Lens NVIP-4H-6202M

Mobile applications SuperLive Plus (iPhone, Android)

VIDEO ANALYTICS

Functions tamper, abandoned object, object disappearance, line cross, zone entrance, multi loiter, scene change, video blurred, video color cast

OTHER FUNCTIONS

Privacy Zones 4 video mask type: single color or 1 video mask type: mosaic

Motion Detection yes

Region of interest (ROI) 3

Image Processing 180° image rotation, sharpening, mirror effect, corridor mode

Prealarm/Postalarm -/up to 120 s

System Reaction to Alarm Events e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation

Restoring default settings via web browser, using reset button, via NMS IPTool software

IR LED

LED Number 4

Range 100 m

Angle 90°

INTERFACES

Video Output BNC, 1.0 Vp-p, 75 Ohm

Alarm Input/Output 1 (NO/NC)/1

Network Interface 1 x Ethernet - RJ-45 interface, 10/100 Mbit/s

Memory Card Slot SD - capacity up to 128GB

INSTALLATION PARAMETERS

Dimensions (mm) with bracket: 109 (Φ) x 360 (L)

Weight 1.7 kg

Degree of Protection IP 66 (details in the user's manual)

Enclosure aluminium, white, fully cable managed wall mount bracket in-set included

Power Supply 12 VDC, PoE (IEEE 802.3af, Class 3)

Surge protection TVS 4000 V

Power Consumption 8 W • 16 W (IR illuminator on)

Operating Temperature -20°C ~ 50°C

Humidity max. 95%, relative (non-condensing)

Some functions are available from 4.2.1 software version