

## Monitor

### SC-24E



#### KEY FEATURES

- dedicated to continuous operation (24/7)
- LED backlight
- Function preventing from burning-in static images on the LCD panel

#### LCD PANEL

|                        |                       |
|------------------------|-----------------------|
| Panel Type             | IPS, LED backlight    |
| Screen Size (Diagonal) | 23.8"                 |
| Panel Resolution       | 1920 x 1080           |
| Format                 | 16:9                  |
| Brightness             | 250 cd/m <sup>2</sup> |
| Contrast Ratio         | 20000000:1            |
| Viewing Angle (H/V)    | 178°/178°             |
| Response Time          | 5 ms                  |
| Display Color          | 16.7 mln              |

#### OTHER FUNCTIONS

|                   |                            |
|-------------------|----------------------------|
| OSD               | languages: English, others |
| Built-in Speakers | 2 x 1 W                    |

#### INTERFACES

|             |                                                           |
|-------------|-----------------------------------------------------------|
| Video Input | 1 x CVBS, BNC connector (loop-through), 1 x VGA, 1 x HDMI |
| Audio Input | 1 x Mini Jack stereo                                      |

#### INSTALLATION PARAMETERS

|                       |                             |
|-----------------------|-----------------------------|
| Dimensions (mm)       | 541 (W) x 397 (H) x 194 (D) |
| Weight                | 3.8 kg                      |
| Case                  | black, plastic              |
| Power Supply          | 100 ~ 240 VAC               |
| Power Consumption     | 22 W (max)                  |
| Operating Temperature | 0°C ~ 40°C                  |
| Mounting Standard     | VESA 100 x 100 mm           |