

Vandal Proof IP Camera with Motor-zoom Lens

NVIP-2V-6402M (NVIP-2DN3032AV/IR-1P)

6000 VSS
IP



KEY FEATURES



- Resolution: 2 MPX
- Lens: motorized, auto-focus function, f=2.8 ~ 12 mm/F1.4
- D/N function - IR cut filter
- Video content analysis
- microSD card support
- WDR with double scan sensor
- Min. Illumination from 0.07 lx (0 lx, IR on)
- IR LED, range up to 30 m

DIMENSIONS



150 mm (Ø)



INFORMATION - The name of the model has changed. The previous name is shown in brackets.

IMAGE

Image Sensor	2 MPX CMOS sensor 1/2.7" APTINA
Number of Effective Pixels	1920 (H) x 1080 (V)
Min. Illumination	0.07 lx/F1.4 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto: 1/3 s ~ 1/100000 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes

LENS

Lens Type	motorized, f=2.8 ~ 12 mm/F1.4
Auto-focus	zoom trigger, day/night mode trigger, manual trigger

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Schedule	yes
Visible Light Sensor	yes

NETWORK

Stream Resolution	1920 x 1080 (Full HD), 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA)
Frame Rate	30 fps for and lower resolutions
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.265, MJPEG/G.711
Number of Simultaneous Connections	max. 4
Bandwidth	9 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, FTP, DHCP, DDNS, NTP, RTSP, UPnP, IEEE 802.1X, PPPoE, SMTP
ONVIF Protocol Support	Profile S
Camera Configuration	from Internet Explorer browser • languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NVR-6000 Viewer
Mobile applications	SuperLive Plus (iPhone, Android)

Vandal Proof IP Camera with Motor-zoom Lens NVIP-2V-6402M (NVIP-2DN3032AV/IR-1P)

VIDEO ANALYTICS

Functions	tamper, line cross, zone entrance, scene change, video blurred, video color cast
-----------	--

OTHER FUNCTIONS

Privacy Zones	4
Motion Detection	yes
Region of interest (ROI)	8
Image Processing	90° image rotation, 180° image rotation, sharpening, mirror effect, corridor mode, horizontal flip
Prealarm/Postalarm	-/up to 120 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation
Restoring default settings	via web browser, using reset button, via NMS IPTool software

IR LED

LED Number	30
Range	30 m
Angle	90°

INTERFACES

Video Output	BNC, 1.0 Vp-p, 75 Ohm
Audio Input/Output	1 x Jack (3.5 mm)/1 x Jack (3.5 mm)
Alarm Input/Output	1 (NO/NC)/1 relay type (max. 12VDC/300mA)
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 128GB

INSTALLATION PARAMETERS

Dimensions (mm)	150 (Φ) x 114 (H)
Weight	1 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	vandalproof, IK10 impact rating, aluminium, white, poly-carbonate bubble
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Power Consumption	2 W • 5 W (IR illuminator on)
Operating Temperature	-30°C ~ 60°C
Humidity	max. 95%, relative (non-condensing)

Specification of the NVIP-2VE-6402M camera as the successor [NVIP-2DN3032AV/IR-1P](#) may be slightly different. Technical data of the [NVIP-2DN3032AV/IR-1P](#) is available [here](#).