NoVus

NMS IP Recorder

NMS NVR 5-4U-II



KEY FEATURES















- •Video and audio channels: 150
- •Recording speed up to 3750 fps at 1920 x 1080
- •Supports resolution up to 4000 x 3000
- •Recorded stream size: 350 Mb/s in total from all cameras
- •Supports up to 3 monitors simultaneously
- •optional disk mounting: 5 x SATA 3,5"
- •Operating system: Microsoft Windows 10 IoT
- •Compatible with all NOVUS IP cameras

DIMENSIONS



VIDEO

| IP Camera Recording | 120 channels at 1920x1080 (video+audio) using H.264 codec • 150 channels at 1920x1080 (video+audio) using H.265 codec |
|--|--|
| Maximum Supported Camera Resolution | 4000x3000 |
| Supported Codes | H.264, H.264+, H.265, H.265+, MJPEG |
| Supported Cameras and Protocols | Novus, Novus fisheye, ONVIF, ONVIF fisheye, RTSP, RTSP fisheye |
| Dualstreaming Support | yes |
| DISPLAY | |
| Monitor Output | 1 x HDMI 2.0b, 1 x Display Port 1.2, 1 x Dual link-DVI (up to 3 monitors simultaneously) |
| Maximum Resolution | 3 x 4K UltraHD |
| AUDIO | |
| Audio input | 1 x Line in (3,5mm), 1 x Mic in(3,5mm) |
| Audio Output | 1 x Line (3,5mm), 1 x HDMI, 1 x Display Port |
| Audio Input/Output in Cameras | Supports audio input/output build in cameras |
| PERFORMANCE - H.264 | |
| 2MPX IP Camera | Recording up to: 120 main streams (while displaying: 8 sub streams) • Display up to: 50 sub streams or 12 main streams (while recording: 50 main streams) • Playback up to: 12 main streams (while recording: 50 main streams) |
| 4MPX IP Camera | Recording up to: 70 main streams (while displaying: 8 sub streams) • Display up to: 45 sub streams or 9 main streams (while recording: 45 main streams) • Playback up to: 8 main streams (while recording: 45 main streams) |
| 5MPX IP Camera | Recording up to: 60 main streams (while displaying: 8 sub streams) • Display up to: 45 sub streams or 6 main streams (while recording: 45 main streams) • Playback up to: 6 main streams (while recording: 45 main streams) |
| 8MPX IP Camera | Recording up to: 40 main streams (while displaying: 8 sub streams) • Display up to: 40 sub streams or 4 main streams (while recording: 4 main streams) • Playback up to: 4 main streams (while recording: 40 main streams) |
| 12MPX IP Camera | Recording up to: 35 main streams (while displaying: 8 sub streams) • Display up to: 35 sub streams or 4 main streams (while recording: 35 main streams) • Playback up to: 4 main streams (while recording: 35 main streams) |
| PERFORMANCE - H.265 | |
| 2MPX IP Camera | Recording up to: 150 main streams (while displaying: 8 sub streams) • Display up to: 30 sub streams or 8 main streams (while recording: 30 main streams) • Playback up to: 8 main streams (while recording: 30 main streams) |



NoVus

NMS IP Recorder NMS NVR 5-4U-II

| 4MPX IP Camera | Recording up to: 100 main streams (while displaying: 8 sub streams) • Display up to: 30 sub streams or 4 main streams (while recording: 30 main streams) • Playback up to: 4 main streams (while recording: 30 main streams) |
|---------------------------------|--|
| 5MPX IP Camera | Recording up to: 80 main streams (while displaying: 8 sub streams) • Display up to: 35 sub streams or 4 main streams (while recording: 35 main streams) • Playback up to: 4 main streams (while recording: 34 main streams) |
| 8MPX IP Camera | Recording up to: 75 main streams (while displaying: 8 sub streams) • Display up to: 35 sub streams or 2 main streams (while recording: 35 main streams) • Playback up to: 2 main streams (while recording: 35 main streams) |
| 12MPX IP Camera | Recording up to: 56 main streams (while displaying: 8 sub streams) • Display up to: 20 sub streams or 2 main streams (while recording: 20 main streams) • Playback up to: 2 main streams (while recording: 20 main streams) |
| RECORDING | |
| Recording Mode | Continuous, Schedule, Panic, Triggered: manually, by alaram input, motion detection, video analysis, POS, temerature alarm |
| Schedule | individual settings for: each camera, each day of the week, specific days (holidays etc.), configuration with an accuracy of: 15 min, possibility of combining individual recording modes |
| Prealarm/Postalarm | Up to: 30s / Up to: 600s |
| PLAYBACK | |
| Recorded Data Search | By Date/Time, Events, "Text-in" |
| DACKUD | |
| BACKUP Backup Methods | USB port (HDD lor Flash drive), Network |
| Backup File Format | IPEG, BMP, AVI, NMS |
| Buckup File Formut | Ji 20, Dilli , AVI, Milo |
| HDD | |
| Internal storage for system | 1 x HDD 3.5" SATA |
| Internal Storage for Recording | 5 available bays for 3,5" HDD surveillance grade storage media |
| ALARMS | |
| Alarm Input/output in cameras | support of alarm input and output built in cameras |
| Motion detection | support of motion detection built in cameras |
| Video Analytics | supported built in analytics in camera |
| Temperature alarm | support of temperature alarm built in cameras |
| Licence plate recognition (LPR) | support of selected image analysis functions available in the camera |
| NETWORK | |
| Network Interface | 1 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s |
| Network Throughput | up to 350Mbit/s from all cameras • up to 350Mbit/s to all client stations • Max network throughput: 350Mbit/s for each network card |
| Network Protocols Support | HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, DHCP, DNS, DDNS, NTP, RTSP, SAMBA |
| Compatible Mobile Applications | NMS Mobile |
| PTZ | |
| PTZ Functions | pan, tilt, zoom, preset commands, patterns, tours, auto-scans, focus, iris |







NMS IP Recorder NMS NVR 5-4U-II

ADDITIONAL INTERFACES

| USB Ports | 6 x USB 3.0 |
|-----------------------------------|---|
| | 0 A 552 515 |
| OPERATING SYSTEM | |
| Operating System | Microsoft Windows 10 IoT |
| Recording and Surveillance System | NMS (Novus Management System) |
| Additional Software | Internet Explorer |
| Operation Mode | Pentaplex |
| OSD | Polish, English, Russian, others |
| Control | PC mouse and keyboard (in-set included), DCZ keyboard |
| System Diagnostic | automatic control of: HDDs, Temperature, Fan, Network, Camera connection loss |
| Security | Password protection, IP filtering, MAC filtering, Limiting the number of connections |
| INTEGRATION | |
| Integrated Devices | Novus IP Cameras, Novus IP Recorders, Novus AHD Recorders, NMS- ANPR Software, DSC Systems, POS Systems (Posnet, Upos and other), ONVIF Devices, RTSP Devices |
| INSTALLATION PARAMETERS | |
| Dimensions (mm) | 427 (W) x 177 (H) x 450 (D) |
| Weight | 20 kg (without HDDs for recording) |
| Power Supply | built in 700W, with 230VAC input |
| Power consumption/heatprint | 260W/210W (without HDD for recording) |
| Operating Temperature | 5°C ~ 35°C |
| RACK Mount 19" | 4U |

Attention:

To support more than 1 RTSP stream and 1 ONVIF stream you will need special licence key. From serial number: XX 2417 4170, devices have Microsoft Windows 10 IoT operating system. Performance specifications described in the above are valid from serial WA 2519 5776

