


NVSO IP Recorder NVSO 3-4U-II



KEY FEATURES



•Video and audio channels: 140

•Recording speed up to 3500 fps at 1920 x 1080 •Supports resolution up to 4000 x 3000 •Recorded stream size: 350 Mb/s in total from all cameras

•Supports up to 3 monitors simultaneously

•optional disk mounting: 5 x SATA 3,5"

•Operating system: Microsoft Windows 10 Pro •Compatible with all NOVUS IP cameras

DIMENSIONS



VIDEO

100 channels at 1920x1080 (video+audio) using H.264 codec \bullet 140 channels at 1920x1080 (video+audio) using H.265 codec
4000x3000
H.264, H.264+, H.265, H.265+, MJPEG
Novus, Novus fisheye, ONVIF, ONVIF fisheye, RTSP, RTSP fisheye
yes
1 x HDMI 2.0b, 1 x Display Port 1.2, 1 x Dual link-DVI (up to 3 monitors simultaneously)
3 x 4K UltraHD
1 x Line in (3,5mm), 1 x Mic in(3,5mm)
1 x Line (3,5mm), 1 x HDMI, 1 x Display Port
Supports audio input/output build in cameras
Recording up to: 100 main streams (while displaying: 8 sub streams) • Display up to: 42 sub streams or 13 main streams (while recording: 42 main streams) • Playback up to: 13 main streams (while recording: 42 main streams)
Recording up to: 65 main streams (while displaying: 8 sub streams) Display up to: 40 sub streams or 7 main streams (while recording: 40 main streams) • Playback up to: 7 main streams (while recording: 40 main streams)
Recording up to: 60 main streams (while displaying: 8 sub streams) Display up to: 35 sub streams or 5 main streams (while recording: 35 main streams) • Playback up to: 5 main streams (while recording: 35 main streams)
Recording up to: 36 main streams (while displaying: 8 sub streams) Display up to: 32 sub streams or 3 main streams (while recording: 32 main streams) • Playback up to: 3 main streams (while recording: 32 main streams)
Recording up to: 32 main streams (while displaying: 8 sub streams) Display up to: 26 sub streams or 3 main streams (while recording: 26 main streams) • Playback up to: 3 main streams (while recording: 26 main streams)
Recording up to: 140 main streams (while displaying: 8 sub streams) • Display up to: 30 sub streams or 6 main streams (while recording: 30 main streams) • Playback up to: 6 main streams (while recording: 30 main streams)





NVSO IP Recorder NVSO 3-4U-II

PTZ Functions	pan, tilt, zoom, preset commands, patterns, tours, auto-scans, focus,
PTZ	
Compatible Mobile Applications	NMS Mobile
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, SAMBA
Network Throughput	up to 350Mbit/s from all cameras • up to 350Mbit/s to all client stations • Max network throughput: 350Mbit/s for each network card
Network Interface	1 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s
NETWORK	
System Reactions to Alarm Events	e-mail, Screen Message, Recording Activation, PTZ
Licence plate recognition (LPR)	support of selected image analysis functions available in the camera
Temperature alarm	support of temperature alarm built in cameras
Video Analytics	supported built in analytics in camera
Motion detection	support of motion detection built in cameras
Alarm Input/output in cameras	support of alarm input and output built in cameras
ALARMS	
Internal Storage for Recording	5 available bays for 3,5" HDD surveillance grade storage media
Internal storage for system	1 x HDD 3.5" SATA
HDD	
Backup File Format	JPEG, BMP, AVI, NMS
Backup Methods	USB port (HDD lor Flash drive), Network
BACKUP	
Recorded Data Search	By Date/Time, Events, "Text-in"
PLAYBACK	
Prealarm/Postalarm	Up to: 30s / Up to: 600s
Schedule	individual settings for: each camera, each day of the week, specific days (holidays etc.), configuration with an accuracy of: 15 min, possibility of combining individual recording modes
Recording Mode	Continuous, Schedule, Panic, Triggered: manually, by alaram input, motion detection, video analysis, POS, temerature alarm
RECORDING	
12MPX IP Camera	Recording up to: 48 main streams (while displaying: 8 sub streams) • Display up to: 20 sub streams or 2 main streams (while recording: 20 main streams) • Playback up to: 2 main streams (while recording: 20 main streams)
	Display up to: 28 sub streams or 2 main streams (while recording: 28 main streams) • Playback up to: 2 main streams (while recording: 28 main streams)
5MPX IP Camera 8MPX IP Camera	Recording up to: 70 main streams (while displaying: 8 sub streams) • Display up to: 30 sub streams or 3 main streams (while recording: 30 main streams) • Playback up to: 3 main streams (while recording: 30 main streams) Recording up to: 60 main streams (while displaying: 8 sub streams) •
4MPX IP Camera	Recording up to: 90 main streams (while displaying: 8 sub streams) • Display up to: 30 sub streams or 3 main streams (while recording: 30 main streams) • Playback up to: 3 main streams (while recording: 30 main streams)





NVSO IP Recorder NVSO 3-4U-II

ADDITIONAL INTERFACES

USB Ports	6 x USB 1.1,	
OPERATING SYSTEM		
Operating System	Microsoft Windows 10 Pro	
Recording and Surveillance System	NMS (Novus Management System)	
Additional Software	Internet Explorer	
Operation Mode	Pentaplex	
OSD	Polish, English, Russian, others	
Control	PC mouse and keyboard (in-set included), DCZ keyboard	
System Diagnostic	automatic control of: HDDs, Temperature, Fan, Network, Camera connection loss	
Security	Password protection, IP filtering, MAC filtering, Limiting the number of connections	

INTEGRATION

Integrated Devices

Novus IP Cameras, Novus IP Recorders, Novus AHD Recorders, NMS-ANPR Software, DSC Systems, POS Systems (Posnet, Upos and other), ONVIF Devices, RTSP Devices

INSTALLATION PARAMETERS

Dimensions (mm)	427 (W) x 177 (H) x 450 (D)
Weight	20 kg (without HDDs for recording)
Power Supply	built in 700W, with 230VAC input
Power consumption/heatprint	250W/200W (without HDD for recording)
Operating Temperature	5°C ~ 35°C
RACK Mount 19"	4U

Attention:

To support more than 1 RTSP stream and 1 ONVIF stream you will need special licence key. From serial number: XX 2417 4170, devices have Microsoft Windows 10 Pro operating system. Performance specifications described in the above are valid from serial WA 2519 5776

