

4-port PoE+ Switch NVS-3304SP



KEY FEATURES



KEY FEATURES

•4 x 100Mbps PoE+ •2 x 100Mb/s UPLINK

DIMENSIONS



PoE+ Ports: 4 x 10/100Mbps (the number of ports simultaneously operating with PoE + mode is limited by PoE budget) • UPLINK ports:
operating with PoE + mode is limited by PoE budget) • UPLINK ports:
2 x 10/100Mbps
IEEE802.3af, Class 3, IEEE802.3at, Class 4
Endspan (1,2+ / 3,6-)
1.2 Gb/s
IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX
1K
Extended mode switch that increases the data and power transmission distance up to 200m (Using 10 Mb/s bandwidth)
Extend
yes
Metal, color navy blue
102 (W) x 22 (H) x 75 (L)
0.3 kg
53 VDC (power supply 100 ~ 240 VAC/53 VDC included)
60 W (maximum)
55 W for ports 1 to 4, up to 30 W for one port
0°C ~ 40°C
0÷85% (relative, non-condensing)

Maximum ranges depend on cable quality, interference and camera model. The ranges were determined in laboratory conditions. For information on the exact ranges for a given camera connection and switches please contact support or perform tests in the real environment of the future operation of the devices.

