

## 4-port PoE+ Switch NVS-3304SP



### KEY FEATURES



### KEY FEATURES

- 4 x 100Mbps PoE+
- 2 x 100Mb/s UPLINK

### DIMENSIONS



### GENERAL

Device Type PoE+ Switch

### NETWORK

|                     |                                                                                                                                                   |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Ports               | PoE+ Ports: 4 x 10/100Mbps (the number of ports simultaneously operating with PoE + mode is limited by PoE budget) • UPLINK ports: 2 x 10/100Mbps |
| PoE standards       | IEEE802.3af, Class 3, IEEE802.3at, Class 4                                                                                                        |
| PoE mode            | Endspan (1,2+ / 3,6-)                                                                                                                             |
| Switching capacity  | 1.2 Gb/s                                                                                                                                          |
| Supported protocols | IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX                                                                                                       |
| MAC address list    | 1K                                                                                                                                                |

### FUNCTIONS

|                            |                                                                                                                 |
|----------------------------|-----------------------------------------------------------------------------------------------------------------|
| CCTV                       | Extend mode switch that increases the data and power transmission distance up to 200m (Using 10 Mb/s bandwidth) |
| Additional operating modes | Extend                                                                                                          |
| Surge protection           | yes                                                                                                             |

### INSTALLATION PARAMETERS

|                       |                                                     |
|-----------------------|-----------------------------------------------------|
| Case                  | Metal, navy blue color                              |
| Dimensions (mm)       | 102 (W) x 22 (H) x 75 (L)                           |
| Weight                | 0.3 kg                                              |
| Input Voltage         | 53 VDC (power supply 100 ~ 240 VAC/53 VDC included) |
| Power Consumption     | 60 W                                                |
| PoE Budget            | 55 W for ports 1 to 4, up to 30 W for one port      |
| Operating Temperature | 0°C ~ 40°C                                          |
| Humidity              | 0÷85% (relative, non-condensing)                    |

Maximum ranges depend on cable quality, interference and camera model. The ranges were determined in laboratory conditions. For information on the exact ranges for a given camera connection and switches please contact support or perform tests in the real environment of the future operation of the devices.