

NVSO Client Station NVSO CLIENT 5-T-II




## **KEY FEATURES**



Monitoring of up to 50 channels
Supports resolution up to 4000 x 3000
Supports up to 3 monitors simultaneously
Operating system: Microsoft Windows 10 Pro
Compatible with all NMS Network Video Recorders
Integration with:recorders AHD NOVUS, systems of
SSWiN DSC, systems of NMS ANPR, systems POS
(Posnet, Upos i inne)

VIDEO

## DIMENSIONS



up to 50 channels at 640 x 480 resolution resolution using H.264 codec (video + audio) $\cdot$ up to 30 channels at 640 x 480 resolution resolution using H.265 codec (video + audio)
4000 x 3000
H.264, H.264+, H.265, H.265+, MJPEG
Novus, ONVIF, RTSP
yes
1 x HDMI 2.0b, 1 x Display Port 1.2, 1 x Dual link-DVI, (up to 3 monitors simultaneously)
3 x 4K UltraHD
1 x Line in (3,5mm), 1 x Mic in(3,5mm)
Display up to: 50 sub streams or 12 main streams • Playback up to: 12 main streams
Display up to: 45 sub streams or 8 main streams • Playback up to: 8 main streams
Display up to: 45 sub streams or 6 main streams • Playback up to: 6 main streams
Display up to: 40 sub streams or 4 main streams • Playback up to: 4 main streams
Display up to: 35 sub streams or 4 main streams • Playback up to: 4 main streams
Display up to: 30 sub streams or 8 main streams • Playback up to: 8 main streams
Display up to: 35 sub streams or 4 main streams • Playback up to: 4 main streams
Display up to: 35 sub streams or 4 main streams • Playback up to: 4 main streams
Display up to: 35 sub streams or 2 main streams • Playback up to: 2 main streams
Display up to: 20 sub streams or 2 main streams • Playback up to: 2 main streams





## NVSO Client Station NVSO CLIENT 5-T-II

Backup Methods	USB port (HDD or Flash memory), network
STORAGE	
Internal storage for system	built-in: 1 x HDD 3,5" SATA
NETWORK	
Network Interface	1 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s
Bandwidth	350 Mb/s in total from all NVRs
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, RTSP, UPnP, SNMP
Mobile applications	NMS Mobile
PTZ	
PTZ Functions	pan/tilt/zoom, preset commands, patterns, tours, auto-scans
AUXILIARY INTERFACES	
USB Ports	6 x USB 3.0,
OPERATING SYSTEM	
Operating System	Microsoft Windows 10 Pro
Operation Mode	triplex
OSD	languages: Polish, English, Russian, others
Control	PC mouse and keyboard (in-set included)
System Diagnostic	automatic control of: HDDs, temperature, fan, network
Security	password protection, IP filtering, MAC filtering, limiting the number of connections
INSTALLATION PARAMETERS	
Dimensions (mm)	160 (W) x 428 (H) x 410 (D)
Weight	10 kg
Power Supply/Power Consumption	built-in PSU 230 VAC/700 W

Attention:

Power consumption/heatprint

Operating Temperature

From serial number: XX 2417 4170, devices have Microsoft Windows 10 Pro operating system. Performance specifications described in the above are valid from serial WA 2519 5776

5°C ~ 35°C

260W/210W (without HDD for recording)

